



DTE2024S48-D Information

Part Number DTE2024S48-D Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC DC CONVERTER 48V 20W

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTE2024S48-D Specifications

Manufacturer Part Number DTE2024S48-D Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DTE20 Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DTE20 Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Manufacturer Part Number	DTE2024S48-D	
Package Module Series DTE20 Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Manufacturer	XP Power	
Package Module Series DTE20 Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series DTE20 Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)		DC DC Converters	
Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Package	Module	
Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Series	DTE20	
Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Type	Isolated	
Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Input (Min)	9V	
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 420mA Power (Watts) 20W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Input (Max)	36V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension	Voltage - Output 1	48V	
Voltage - Output 4 Current - Output (Max) 420mA Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension -40°C ~ 85°C Module 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 2	-	
Current - Output (Max) 420mA Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 420mA 20W ITE (Commercial) -40°C ~ 85°C By 600 Applications Applications ITE (Commercial) -40°C ~ 85°C By 600 Applications 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 20W ITE (Commercial) -40°C ~ 85°C DIN Rail DIN Rail And DIN Rail Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Current - Output (Max)	420mA	
Operating Temperature -40°C ~ 85°C Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Power (Watts)	20W	
Efficiency 89% Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Applications	ITE (Commercial)	
Mounting Type DIN Rail Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Operating Temperature	-40°C ~ 85°C	
Package / Case Module Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Efficiency	89%	
Size / Dimension 3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	Mounting Type	DIN Rail	
	Package / Case	Module	
Report errors?	Size / Dimension	3.78" L x 2.13" W x 0.92" H (96.0mm x 54.0mm x 23.3mm)	
		Report error	ors?

DTE2024S48-D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTE2024S48-D Payment Methods



















DTE2024S48-D Shipping Methods













If you have any question about DTE2024S48-D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com