



DTE4048S48 Information



For Reference Only

Part Number DTE4048S48 Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC DC CONVERTER 48V 40W

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTE4048S48 Specifications

Manufacturer Part Number DTE4048S48 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DTE40 Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module Size / Dimension 4.41" L x 2.51" W x 1.01" H (112.0mm x 63.8mm x 25.6mm)	•	
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DTE40 Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Manufacturer Part Number	DTE4048S48
Package Module Series DTE40 Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Manufacturer	XP Power
Package Module Series DTE40 Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Category	Power Supplies - External/Internal (Off-Board)
Series DTE40 Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module		DC DC Converters
Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Package	Module
Voltage - Input (Min) 18V Voltage - Input (Max) 75V Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Series	DTE40
Voltage - Input (Max) Number of Outputs 1 Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Type	Isolated
Number of Outputs 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Voltage - Input (Min)	18V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 835mA Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Voltage - Input (Max)	75V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency Mounting Type Chassis Mount Package / Case Poutput 2	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency Mounting Type Chassis Mount Package / Case Module	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) 835mA Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Voltage - Output 3	-
Power (Watts) 40W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Current - Output (Max)	835mA
Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Power (Watts)	40W
Efficiency 90% Mounting Type Chassis Mount Package / Case Module	Applications	ITE (Commercial)
Mounting Type Chassis Mount Package / Case Module	Operating Temperature	-40°C ~ 85°C
Package / Case Module	Efficiency	
		Chassis Mount
Size / Dimension 4.41" L x 2.51" W x 1.01" H (112.0mm x 63.8mm x 25.6mm)	Package / Case	
	Size / Dimension	4.41" L x 2.51" W x 1.01" H (112.0mm x 63.8mm x 25.6mm)
Report errors		Report errors?

DTE4048S48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTE4048S48 Payment Methods





















DTE4048S48 Shipping Methods













If you have any question about DTE4048S48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com