



### DTM110PW120C Information



For Reference Only

Part Number DTM110PW120C

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 90W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DTM110PW120C Specifications**

Manufacturer Part Number         DTM110PW120C           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           Rekage         -           Series         DTM110-C           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         7.5A           Power (Watts)         90W           No Load Power Consumption         -           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         DTM110-C           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         7.5A           Power (Watts)         90W           No Load Power Consumption         -           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Manufacturer Part Number	DTM110PW120C
Package         -           Series         DTM110-C           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         7.5A           Power (Watts)         90W           No Load Power Consumption         -           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         DTM110-C           Region Utilized         International           Form         Desktop (Class I)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         7.5A           Power (Watts)         90W           No Load Power Consumption         -           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesDTM110-CRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7.5APower (Watts)90WNo Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7.5APower (Watts)90WNo Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 7.5A  Power (Watts) 90W  No Load Power Consumption -  Polarization - Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Series	DTM110-C
Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 7.5A  Power (Watts) 90W  No Load Power Consumption -  Polarization -  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Region Utilized	International
Voltage - Input  90 ~ 264 VAC  Voltage - Output  12V  Current - Output (Max)  7.5A  Power (Watts)  90W  No Load Power Consumption  - Polarization  - Applications  Medical  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  90 ~ 264 VAC  12V  7.5A  90W  No Load Power Consumption  - Cons	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 7.5A  Power (Watts) 90W  No Load Power Consumption - Polarization - Applications  Efficiency Operating Temperature  O°C ~ 40°C  Output Connector  Power La 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)  7.5A  Power (Watts)  90W  No Load Power Consumption  - Polarization  Applications  Medical  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  7.5A  7.5A  7.5A  90W  No Load Power Consumption  - Consumption  - Consumption  Nedical  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 90W  No Load Power Consumption -  Polarization -  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Voltage - Output	12V
No Load Power Consumption  Polarization  Applications  Medical  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Current - Output (Max)	7.5A
Polarization - Medical Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.70^{\circ}\text{L} \times 2.55^{\circ}\text{W} \times 1.52^{\circ}\text{H} (170.0 \text{mm} \times 64.8 \text{mm} \times 38.5 \text{mm})$	Power (Watts)	90W
Applications Medical Efficiency Level V   Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin   Size / Dimension $6.70^{\circ}\text{L} \times 2.55^{\circ}\text{W} \times 1.52^{\circ}\text{H} (170.0 \text{mm} \times 64.8 \text{mm} \times 38.5 \text{mm})$	No Load Power Consumption	-
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension $6.70^{\circ}\text{L x } 2.55^{\circ}\text{W x } 1.52^{\circ}\text{H } (170.0\text{mm x } 64.8\text{mm x } 38.5\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.70^{\circ}\text{L x } 2.55^{\circ}\text{W x } 1.52^{\circ}\text{H } (170.0\text{mm x } 64.8\text{mm x } 38.5\text{mm})$	Applications	Medical
Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Efficiency	Level V
Size / Dimension 6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.70" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)
		Report errors?

### DTM110PW120C Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DTM110PW120C Payment Methods



















## DTM110PW120C Shipping Methods













If you have any question about DTM110PW120C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com