



DTM165PW240C Information

w.h sener.com

Part Number DTM165PW240C

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 165W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTM165PW240C Specifications

Manufacturer Part Number DTM165PW240C Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series DTM165-C Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series DTM165-C Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer Part Number	DTM165PW240C
Package - Series DTM165-C Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series DTM165-C Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesDTM165-CRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.88APower (Watts)165WNo Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)6.88APower (Watts)165WNo Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24V$ Current - Output (Max) $6.88A$ Power (Watts) $165W$ No Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorPower DIN, 4 PinSize / Dimension 6.69° L x 3.35° W x 1.73° H (170.0mm x 85.0 mm x 44.0 mm)	Series	DTM165-C
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{W} \times 1.73^{\circ}\text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Efficiency Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 24V 6.88A 165W Medical - Level V Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 6.88A Power (Watts) 165W No Load Power Consumption - Polarization - Applications Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $165W$ No Load Power Consumption-Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension 6.69 " L x 3.35 " W x 1.73 " H (170.0mm x 85.0 mm x 44.0 mm)	Voltage - Output	24V
No Load Power Consumption - Polarization - Medical Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{W} \times 1.73^{\circ}\text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Current - Output (Max)	6.88A
Polarization - Medical Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L} \times 3.35^{\circ}\text{W} \times 1.73^{\circ}\text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Power (Watts)	165W
Applications Medical Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 6.69° L x 3.35° W x 1.73° H (170.0mm x 85.0 mm x 44.0 mm)	No Load Power Consumption	-
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Applications	Medical
Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Efficiency	Level V
Size / Dimension 6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.69" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)
		Report errors?

DTM165PW240C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTM165PW240C Payment Methods



















DTM165PW240C Shipping Methods













If you have any question about DTM165PW240C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com