



DTM65PW280C8 Information

Part Number DTM65PW280C8

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 28V 65W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTM65PW280C8 Specifications

Manufacturer Part Number DTM65PW280C8 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series DTM65-C8 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 4.17" L x 2.36" W x 1.22" H (106.0mm x 60.0mm x 31.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series DTM65-C8 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) No Load Power Consumption Polarization - Applications Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin	Manufacturer Part Number	DTM65PW280C8
Package - Series DTM65-C8 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 2.32A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin	Manufacturer	TDK-Lambda Americas Inc.
Package-SeriesDTM65-C8Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output28VCurrent - Output (Max)2.32APower (Watts)65WNo Load Power Consumption210mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 Pin	Category	Power Supplies - External/Internal (Off-Board)
SeriesDTM65-C8Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output28VCurrent - Output (Max)2.32APower (Watts)65WNo Load Power Consumption210mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 Pin		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin	Series	DTM65-C8
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 28V Current - Output (Max) 2.32A Power (Watts) 65W No Load Power Consumption 210mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 Pin	Form	Desktop (Class II)
Voltage - Output (Max) Current - Output (Max) Power (Watts) No Load Power Consumption 210mW (Max) Polarization - Applications Medical Efficiency Level VI Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications Medical Efficiency Operating Temperature O°C ~ 60°C Output Connector Power DIN, 4 Pin	Voltage - Input	90 ~ 264 VAC
Power (Watts) $65W$ No Load Power Consumption $210mW$ (Max)Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorPower DIN, 4 Pin	Voltage - Output	28V
No Load Power Consumption 210mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 Pin	Current - Output (Max)	2.32A
Polarization-ApplicationsMedicalEfficiencyLevel VIOperating Temperature 0° C $\sim 60^{\circ}$ COutput ConnectorPower DIN, 4 Pin	Power (Watts)	65W
Applications Medical Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin	No Load Power Consumption	210mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin	Applications	Medical
Output Connector Power DIN, 4 Pin	Efficiency	Level VI
•	Operating Temperature	0°C ~ 60°C
Size / Dimension 4.17" L x 2.36" W x 1.22" H (106.0mm x 60.0mm x 31.0mm)	Output Connector	Power DIN, 4 Pin
	Size / Dimension	4.17" L x 2.36" W x 1.22" H (106.0mm x 60.0mm x 31.0mm)
Report errors?		Report errors?

DTM65PW280C8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTM65PW280C8 Payment Methods





















DTM65PW280C8 Shipping Methods













If you have any question about DTM65PW280C8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com