

DTR050100-P12/RN

DTR050100-P12/RN Information

Heisener.com

Part Number DTR050100-P12/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 5V 5W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTR050100-P12/RN Specifications

Manufacturer Part NumberDTR050100-P12/RNManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)1APower (Watts)5WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mmSize / Dimension3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Manufacturer Part Number	DTR050100-P12/RN
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Series	-
Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 120VAC 14 120VAC 14 15 Voltage - Input 14 15 Voltage - Output (Max) 15 Voltage - Output (Max) 16 17 18 18 18 18 18 18 18 18 18	Form	Desktop (Class II)
Voltage - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Input Type	Cord
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Voltage - Input	120VAC
Power (Watts) 5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Voltage - Output	5V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Current - Output (Max)	1A
Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Power (Watts)	5W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Polarization	Negative Center
Operating Temperature Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Efficiency	-
Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 0.7mm I.D. x 2.4mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)
		Report errors?

DTR050100-P12/RN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTR050100-P12/RN Payment Methods



















DTR050100-P12/RN Shipping Methods













If you have any question about DTR050100-P12/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com