



### DTR050100-P6P Information

Heisener.com

Part Number DTR050100-P6P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 5V 5W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DTR050100-P6P Specifications**

Manufacturer Part Number         DTR050100-P6P           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output (Max)         1A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Manufacturer Part Number	DTR050100-P6P
Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1A           Power (Watts)         5W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)1APower (Watts)5WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1A Power (Watts) 5W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Series	-
Input Type Cord  Voltage - Input 120VAC  Voltage - Output 5V  Current - Output (Max) 1A  Power (Watts) 5W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 56.0mm)	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  5V  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  120VAC  14  120VAC  14  15  Voltage - Input  14  15  Voltage - Output (Max)  14  15  Voltage - Output (Max)  16  17  18  18  18  18  19  19  10  10  10  10  10  10  10  10	Form	Desktop (Class II)
Voltage - Output (Max) 1A  Power (Watts) 5W  No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Input Type	Cord
Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  1A  5W  5W  Center  ITE (Commercial)  -  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Voltage - Input	120VAC
Power (Watts) 5W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Voltage - Output	5V
No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Current - Output (Max)	1A
Polarization Positive Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Power (Watts)	5W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Polarization	Positive Center
Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Efficiency	-
Size / Dimension 3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	3.35" L x 2.68" W x 2.20" H (85.0mm x 68.0mm x 56.0mm)
		Report errors?

#### DTR050100-P6P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DTR050100-P6P Payment Methods



















# DTR050100-P6P Shipping Methods













If you have any question about DTR050100-P6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com