



# DTR050150-Z5N Information

Heisener.com

Part Number DTR050150-Z5N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 8W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DTR050150-Z5N Specifications

Manufacturer Part Number     DTR050150-Z5N       Manufacturer     CUI Inc.       Category     Power Supplies - External/Internal (Off-Board)       AC DC Desktop, Wall Adapters       Package     -       Series     -       Region Utilized     North America       Form     Desktop (Class II)       Input Type     Fixed Blade       Voltage - Input     120VAC       Voltage - Output     5V       Current - Output (Max)     1.5A       Power (Watts)     7.5W       No Load Power Consumption     -       Polarization     Negative Center       Applications     ITE (Commercial)       Efficiency     -       Operating Temperature     -       Output Connector     Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm       Size / Dimension     4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Manufacturer Part Number	DTR050150-Z5N
Package-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)7.5WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeFixed BladeVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)7.5WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Package	-
Form Desktop (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Series	-
Input TypeFixed BladeVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)1.5APower (Watts)7.5WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  5V  Current - Output (Max)  1.5A  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  120VAC  1.5A  1.5A  7.5W  No Load Power Consumption  - Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Form	Desktop (Class II)
Voltage - Output (Max) 1.5A  Power (Watts) 7.5W  No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  7.5W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Voltage - Input	120VAC
Power (Watts)  7.5W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Voltage - Output	5V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Current - Output (Max)	1.5A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Power (Watts)	7.5W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Polarization	Negative Center
Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Efficiency	-
Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)
Transfer of the contract of th		Report errors?

#### DTR050150-Z5N Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DTR050150-Z5N Payment Methods



















# DTR050150-Z5N Shipping Methods













If you have any question about DTR050150-Z5N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com