

Heisener.com

# DTS050400U2/AC1-Z6N

### DTS050400U2/AC1-Z6N Information

Part Number DTS050400U2/AC1-Z6N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 5V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DTS050400U2/AC1-Z6N Specifications

| Manufacturer Part NumberDTS050400U2/AC1-Z6NManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70% |
|---|
| Category Power Supplies - External/Internal (Off-Board)  AC DC Desktop, Wall Adapters  Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption - Polarization Negative Center  Applications ITE (Commercial)   |
| AC DC Desktop, Wall Adapters  Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W  No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)   |
| Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  |
| Series - Region Utilized - Desktop (Class II)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption - Polarization Negative Center  Applications ITE (Commercial)  |
| Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  |
| Form Desktop (Class II)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)   |
| Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  |
| Voltage - Input  90 ~ 264 VAC  Voltage - Output  5V  Current - Output (Max)  4A  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  |
| Voltage - Output 5V  Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)   |
| Current - Output (Max) 4A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  |
| Power (Watts)  No Load Power Consumption  Polarization  Applications  Negative Center  ITE (Commercial)   |
| No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  |
| Polarization Negative Center Applications ITE (Commercial)  |
| Applications ITE (Commercial)   |
|   |
| Efficiency 70%  |
|   |
| Operating Temperature -   |
| Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  |
| Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)  |
| Report error  |

#### DTS050400U2/AC1-Z6N Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DTS050400U2/AC1-Z6N Payment Methods



















### DTS050400U2/AC1-Z6N Shipping Methods













If you have any question about DTS050400U2/AC1-Z6N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com