

Heisener.com

DTS050400UC-P5P-KH

DTS050400UC-P5P-KH Information

Part Number DTS050400UC-P5P-KH

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 5V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS050400UC-P5P-KH Specifications

Manufacturer Part Number DTS050400UC-PSP-KH Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Manufacturer Part Number	DTS050400UC-P5P-KH
Package-Series-Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $4.33^{\circ}\text{ L x } 2.24^{\circ}\text{ W x } 1.38^{\circ}\text{ H } (110.0\text{mm x } 57.0\text{mm x } 35.0\text{mm})$	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{ mm I.D. x } 5.5 \text{ mm O.D. x } 9.5 \text{ mm}$ Size / Dimension $4.33^{\circ}\text{L x } 2.24^{\circ}\text{W x } 1.38^{\circ}\text{H } (110.0 \text{mm x } 57.0 \text{mm x } 35.0 \text{mm})$	Series	-
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Region Utilized	International
Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 100 ~ 240 VAC 5V Current - Output (Max) 4A Power 100 ~ 240 VAC 100 ~ 240 V	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 4A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5V Current - Output (Max) 4A Power (Watts) Power (Watts) Positive Center ITE (Commercial) 70% Overating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) $20W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, $2.1 \text{mm I.D. x 5.5mm O.D. x 9.5mm}$ Size / Dimension 4.33 " L x 2.24 " W x 1.38 " H ($110.0 mm x 57.0 mm x 35.0 mm$)	Voltage - Output	5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 4.33 " L x 2.24 " W x 1.38 " H ($110.0 \text{mm x } 57.0 \text{mm x } 35.0 \text{mm}$)	Current - Output (Max)	4A
Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.24^{\circ}\text{W} \times 1.38^{\circ}\text{H} (110.0 \text{mm} \times 57.0 \text{mm} \times 35.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.24^{\circ}\text{W} \times 1.38^{\circ}\text{H} (110.0\text{mm} \times 57.0\text{mm} \times 35.0\text{mm})$	No Load Power Consumption	-
Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Polarization	Positive Center
$ \begin{array}{lll} \mbox{Operating Temperature} & 0^{\circ}\mbox{C} \sim 40^{\circ}\mbox{C} \\ \mbox{Output Connector} & \mbox{Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm} \\ \mbox{Size / Dimension} & 4.33" \mbox{ L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)} \\ \end{array} $	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Efficiency	70%
Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)
		Report errors?

DTS050400UC-P5P-KH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS050400UC-P5P-KH Payment Methods



















DTS050400UC-P5P-KH Shipping Methods













If you have any question about DTS050400UC-P5P-KH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com