

Heisener.com

DTS050400UDC-P7/RP

DTS050400UDC-P7/RP Information

Part Number DTS050400UDC-P7/RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 5V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS050400UDC-P7/RP Specifications

Manufacturer Part NumberDTS050400UDC-P7/RPManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS050400UDC-P7/RP
Package-Series-Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
FormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $4A$ Power (Watts) $20W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension 4.33 " L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Series	-
Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 4A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max) 4A Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 20W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Output	5V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	4A
Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	70%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
Report chois:		Report errors?

DTS050400UDC-P7/RP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS050400UDC-P7/RP Payment Methods





















DTS050400UDC-P7/RP Shipping Methods













If you have any question about DTS050400UDC-P7/RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com