

# **DTS060330UDC-P7N**

### DTS060330UDC-P7N Information

Heisener.com

Part Number DTS060330UDC-P7N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 6V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DTS060330UDC-P7N Specifications

| Manufacturer Part Number         DTS060330UDC-P7N           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6V           Current - Output (Max)         3.3A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         60%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)    Report errors? |                           |   |
|---|---------------------------|---|
| Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6V           Current - Output (Max)         3.3A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         60%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | Manufacturer Part Number  | DTS060330UDC-P7N  |
| Package-Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)3.3APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency60%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | Manufacturer              | CUI Inc.  |
| Package         -           Series         -           Region Utilized         International           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         6V           Current - Output (Max)         3.3A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         60%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Category                  | Power Supplies - External/Internal (Off-Board)          |
| Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)3.3APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency60%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   |                           | AC DC Desktop, Wall Adapters                            |
| Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | Package                   | -   |
| Form Desktop (Class II) Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 6V Current - Output (Max) 3.3A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 60%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | Series                    | -   |
| Input Type Cord (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 6V  Current - Output (Max) 3.3A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 60%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Region Utilized           | International   |
| Voltage - Input 90 ~ 264 VAC  Voltage - Output 6V  Current - Output (Max) 3.3A  Power (Watts) 20W  No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  Efficiency 60% Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Form                      | Desktop (Class II)                                      |
| Voltage - Output  Current - Output (Max)  3.3A  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Input Type                | Cord (Sold Separately)                                  |
| Current - Output (Max)  3.3A  Power (Watts)  20W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  60%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Voltage - Input           | 90 ~ 264 VAC  |
| Power (Watts)  20W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  60%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Voltage - Output          | 6V  |
| No Load Power Consumption  Polarization  Negative Center  ITE (Commercial)  Efficiency  60%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Current - Output (Max)    | 3.3A  |
| Polarization Negative Center  Applications ITE (Commercial)  Efficiency 60%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension $4.33'' \text{L} \times 2.36'' \text{W} \times 1.34'' \text{H} (110.0 \text{mm} \times 60.0 \text{mm} \times 34.0 \text{mm})$   | Power (Watts)             | 20W   |
| Applications ITE (Commercial)  Efficiency 60%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | No Load Power Consumption | -   |
| Efficiency 60% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$  | Polarization              | Negative Center   |
|   | Applications              | ITE (Commercial)  |
| Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)   | Efficiency                | 60%   |
| Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)  | Operating Temperature     | 10°C ~ 40°C   |
|   | Output Connector          | Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm            |
| Report errors?  | Size / Dimension          | 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm) |
|   |                           | Report errors?  |

### DTS060330UDC-P7N Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DTS060330UDC-P7N Payment Methods



















## DTS060330UDC-P7N Shipping Methods













If you have any question about DTS060330UDC-P7N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com