

Heisener.com

DTS060330UDC-P9/RN

DTS060330UDC-P9/RN Information

Part Number DTS060330UDC-P9/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 6V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS060330UDC-P9/RN Specifications

Manufacturer Part Number DTS060330UDC-P9/RN Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS060330UDC-P9/RN
Package-Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)3.3APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency60%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)3.3APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency60%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)3.3APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency60%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Series	-
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 3.3A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.3A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Output	6V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	3.3A
Polarization Negative Center Applications ITE (Commercial) Efficiency 60% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33° L x 2.36° W x 1.34° H (110.0mm x 60.0mm x 34.0mm)	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 60% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. $\times 3.8\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension 4.33° L $\times 2.36^{\circ}$ W $\times 1.34^{\circ}$ H (110.0mm $\times 60.0\text{mm}$ $\times 34.0\text{mm}$)	No Load Power Consumption	-
Efficiency 60% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33° L x 2.36° W x 1.34° H (110.0mm x 60.0mm x 34.0mm)	Polarization	Negative Center
Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm $\text{Size / Dimension} \qquad 4.33\text{" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)}$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	60%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
		Report errors?

DTS060330UDC-P9/RN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS060330UDC-P9/RN Payment Methods



















DTS060330UDC-P9/RN Shipping Methods













If you have any question about DTS060330UDC-P9/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com