

Heisener.com

DTS090220U2/AC1-Z5N

DTS090220U2/AC1-Z5N Information

Part Number DTS090220U2/AC1-Z5N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 9V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS090220U2/AC1-Z5N Specifications

Manufacturer Part Number DTS090220U2/AC1-Z5N Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Manufacturer Part Number	DTS090220U2/AC1-Z5N
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $9V$ Current - Output (Max) $2.2A$ Power (Watts) $20W$ No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{rmm I.D. x } 5.5 \text{rmm } O.D. x 9.5 \text{rmm}$ Size / Dimension $4.45^{\circ}\text{L x } 2.40^{\circ}\text{W x } 1.34^{\circ}\text{H } (113.0 \text{mm x } 34.0 \text{mm})$	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0° C ~ 45° C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45° L x 2.40° W x 1.34° H (113.0mm x 61.0 mm x 34.0 mm)	Series	-
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $4.45^{\circ}\text{L x } 2.40^{\circ}\text{ W x } 1.34^{\circ}\text{ H } (113.0\text{mm x } 61.0\text{mm x } 34.0\text{mm})$	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 90 ~ 264 VAC 9V Current - Output (Max) 9V Current - Output (Max) 2.2A No Load Power Consumption - Negative Center 1TE (Commercial) 1TE (Commercial) 1TE (Commercial) 2TE (Commercial) 4.45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.45°L x 2.40°W x 1.34°H (113.0mm x 61.0mm x 34.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 2.2A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 9V 2.2A 2.0W No Load Power Consumption - Negative Center ITE (Commercial) 70% Overating Temperature O°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $20W$ No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature 0° C ~ 45° COutput ConnectorBarrel Plug, 2.1 mm I.D. x 5.5 mm O.D. x 9.5 mmSize / Dimension 4.45 " L x 2.40 " W x 1.34 " H (113.0 mm x 61.0 mm x 34.0 mm)	Voltage - Output	9V
No Load Power Consumption Polarization Negative Center ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Current - Output (Max)	2.2A
Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension $4.45^{\circ}\text{L x } 2.40^{\circ}\text{W x } 1.34^{\circ}\text{H } (113.0 \text{mm x } 34.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.45^{\circ}\text{L} \times 2.40^{\circ}\text{W} \times 1.34^{\circ}\text{H} (113.0\text{mm} \times 34.0\text{mm})$	No Load Power Consumption	-
Efficiency 70% Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45 " L x 2.40 " W x 1.34 " H (113.0mm x 61.0 mm x 34.0 mm)	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.45^{\circ}\text{L} \times 2.40^{\circ}\text{W} \times 1.34^{\circ}\text{H} (113.0\text{mm} \times 34.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Efficiency	70%
Size / Dimension 4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)	Operating Temperature	0°C ~ 45°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.45" L x 2.40" W x 1.34" H (113.0mm x 61.0mm x 34.0mm)
		Report errors?

DTS090220U2/AC1-Z5N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS090220U2/AC1-Z5N Payment Methods



















DTS090220U2/AC1-Z5N Shipping Methods













If you have any question about DTS090220U2/AC1-Z5N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com