

DTS090220UDC-P7N

DTS090220UDC-P7N Information

Heisener.com

Part Number DTS090220UDC-P7N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 9V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS090220UDC-P7N Specifications

Manufacturer Part Number DTS090220UDC-P7N Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS090220UDC-P7N
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output9VCurrent - Output (Max)2.2APower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency65%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Series	-
Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 9V Current - Output (Max) 2.2A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Form	Desktop (Class II)
Voltage - Output (Max) 2.2A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max) 2.2A Power (Watts) No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 20W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Output	9V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	2.2A
Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0 \text{mm} \times 60.0 \text{mm} \times 34.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	No Load Power Consumption	-
Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	65%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
		Report errors?

DTS090220UDC-P7N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS090220UDC-P7N Payment Methods





















DTS090220UDC-P7N Shipping Methods













If you have any question about DTS090220UDC-P7N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com