

Heisener.com

DTS120100SUDC-P5N

DTS120100SUDC-P5N Information

Part Number DTS120100SUDC-P5N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS120100SUDC-P5N Specifications

Manufacturer Part Number DTS120100SUDC-PSN Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Manufacturer Part Number	DTS120100SUDC-P5N
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Package	-
FormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $1A$ Power (Watts) $12W$ No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{ mm I.D. x } 5.5 \text{ mm O.D. x } 9.5 \text{ mm}$ Size / Dimension $2.91^{\circ}\text{ L x } 1.81^{\circ}\text{ W x } 0.98^{\circ}\text{ H } (74.0 \text{ mm x } 46.0 \text{ mm x } 25.0 \text{ mm})$	Series	-
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) $1A$ Power (Watts) 12W No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension $2.91^{\circ}\text{ L x } 1.81^{\circ}\text{ W x } 0.98^{\circ}\text{ H } (74.0 \text{mm x } 46.0 \text{mm x } 25.0 \text{mm})$	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 1A Power (Watts) 12W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 12V 12V 12V 12W 12W No Load Power Consumption - Negative Center Negative Center 17E (Commercial) 17E (Commercial) 20°C ~ 40°C 17E (Commercial) 17E (Commercial)	Input Type	Cord
Current - Output (Max) Power (Watts) 12W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 12W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Voltage - Output	12V
No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug, 2.1 mm I.D. x 5.5 mm $0.D. x$ 9.5 mmSize / Dimension 2.91 " L x 1.81 " W x 0.98 " H $(74.0$ mm x 46.0 mm x 25.0 mm)	Current - Output (Max)	1A
PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x 5.5 mm O.D. x 9.5 mm}$ Size / Dimension 2.91 " L x 1.81 " W x 0.98 " H $(74.0 \text{mm x 46.0 mm x 25.0 mm})$	Power (Watts)	12W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Efficiency	70%
Size / Dimension 2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.91" L x 1.81" W x 0.98" H (74.0mm x 46.0mm x 25.0mm)
		Report errors?

DTS120100SUDC-P5N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS120100SUDC-P5N Payment Methods



















DTS120100SUDC-P5N Shipping Methods













If you have any question about DTS120100SUDC-P5N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com