

Heisener.com

# **DTS120166UDC-P14/RN**

#### DTS120166UDC-P14/RN Information

Part Number DTS120166UDC-P14/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 12V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DTS120166UDC-P14/RN Specifications

Manufacturer Part Number         DTS120166UDC-P14/RN           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS120166UDC-P14/RN
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.66A           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
FormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12\text{V}$ Current - Output (Max) $1.66\text{A}$ Power (Watts) $20\text{W}$ No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency $70\%$ Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $1.7\text{mm I.D. x } 4.8\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $4.33$ " L x $2.36$ " W x $1.34$ " H ( $110.0\text{mm x } 60.0\text{mm x } 34.0\text{mm}$ )	Series	-
Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.66A  Power (Watts) 20W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	-
Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.66A  Power (Watts) 20W  No Load Power Consumption - Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70% Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 1.66A Power (Watts) 20W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max)  1.66A  Power (Watts)  20W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  20W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Output	12V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	1.66A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0 \text{mm} \times 60.0 \text{mm} \times 34.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension $4.33^{\circ}\text{L x } 2.36^{\circ}\text{W x } 1.34^{\circ}\text{H } (110.0\text{mm x } 60.0\text{mm x } 34.0\text{mm})$	No Load Power Consumption	-
Efficiency 70%   Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm   Size / Dimension $4.33^{\circ}\text{L x } 2.36^{\circ}\text{W x } 1.34^{\circ}\text{H } (110.0\text{mm x } 60.0\text{mm x } 34.0\text{mm})$	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	70%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 1.7mm I.D. x 4.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
		Report errors?

### DTS120166UDC-P14/RN Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DTS120166UDC-P14/RN Payment Methods





















## DTS120166UDC-P14/RN Shipping Methods













If you have any question about DTS120166UDC-P14/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com