

Heisener.com

DTS120200UC-P5P-KH

DTS120200UC-P5P-KH Information

Part Number DTS120200UC-P5P-KH

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 24W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS120200UC-P5P-KH Specifications

Manufacturer Part Number DTS120200UC-PSP-KH Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Manufacturer Part Number	DTS120200UC-P5P-KH
Package-Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output12VCurrent - Output (Max)2APower (Watts)24WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency78%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x 5.5mm O.D. x 9.5mm}$ Size / Dimension $4.33^{\circ}\text{L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)}$		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{ mm I.D. x 5.5 mm O.D. x 9.5 mm}$ Size / Dimension $4.33^{\circ}\text{L x 2.24^{\circ} W x 1.38^{\circ} H (110.0 mm x 57.0 mm x 35.0 mm)}$	Series	-
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Region Utilized	International
Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 12V 12V 12V 12V 12V 24W 14W 15W 15W 15W 15W 15W 15W 1	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Voltage - Output	12V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 4.33 " L x 2.24 " W x 1.38 " H ($110.0 \text{mm x } 57.0 \text{mm x } 35.0 \text{mm}$)	Current - Output (Max)	2A
Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Power (Watts)	24W
Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	No Load Power Consumption	-
Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Polarization	Positive Center
$ \begin{array}{lll} \mbox{Operating Temperature} & 0^{\circ}\mbox{C} \sim 40^{\circ}\mbox{C} \\ \mbox{Output Connector} & \mbox{Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm} \\ \mbox{Size / Dimension} & 4.33" \mbox{ L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)} \\ \end{array} $	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Efficiency	78%
Size / Dimension 4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.33" L x 2.24" W x 1.38" H (110.0mm x 57.0mm x 35.0mm)
		Report errors?

DTS120200UC-P5P-KH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS120200UC-P5P-KH Payment Methods



















DTS120200UC-P5P-KH Shipping Methods













If you have any question about DTS120200UC-P5P-KH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com