

DTS120200UDC-P5P-TK

DTS120200UDC-P5P-TK Information



For Reference Only

Part Number DTS120200UDC-P5P-TK

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 24W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS120200UDC-P5P-TK Specifications

Manufacturer Part Number DTS 120200UDC-P5P-TK Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Manufacturer Part Number	DTS120200UDC-P5P-TK
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)2APower (Watts)24WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency75%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $4.13^{\circ}\text{ L x } 1.91^{\circ}\text{ W x } 1.39^{\circ}\text{ H } (105.0\text{mm x } 48.5\text{mm x } 35.2\text{mm})$	Package	-
FormDesktop (Class II)Input Type $Cord$ (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $2A$ Power (Watts) $24W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 75% Operating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.1 rm m I.D. x 5.5 rm O.D. x 9.5 rm m m m x 48.5 rm x 35.2 rm m x 35.2 rm m x 35.2 rm m x 35.2 rm$	Series	-
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{ mm I.D. x } 5.5 \text{ mm } O.D. x } 9.5 \text{ mm}$ Size / Dimension $4.13^{\circ}\text{ L x } 1.91^{\circ}\text{ W x } 1.39^{\circ}\text{ H } (105.0 \text{ mm x } 48.5 \text{ mm x } 35.2 \text{ mm})$	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 2A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Polarization Applications Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2A Power (Watts) 24W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $24W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 4.13 " L x 1.91 " W x 1.39 " H ($105.0 \text{mm x } 48.5 \text{mm x } 35.2 \text{mm}$)	Voltage - Output	12V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 4.13 " L x 1.91 " W x 1.39 " H ($105.0 \text{mm x } 48.5 \text{mm x } 35.2 \text{mm}$)	Current - Output (Max)	2A
Polarization Positive Center Applications ITE (Commercial) Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension $4.13^{\circ}\text{L x } 1.91^{\circ}\text{W x } 1.39^{\circ}\text{H } (105.0 \text{mm x } 48.5 \text{mm x } 35.2 \text{mm})$	Power (Watts)	24W
Applications ITE (Commercial) Efficiency 75% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.13^{\circ}\text{L} \times 1.91^{\circ}\text{W} \times 1.39^{\circ}\text{H} (105.0\text{mm} \times 48.5\text{mm} \times 35.2\text{mm})$	No Load Power Consumption	-
Efficiency 75% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. \times 5.5mm O.D. \times 9.5mm Size / Dimension 4.13" L \times 1.91" W \times 1.39" H (105.0mm \times 48.5mm \times 35.2mm)	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Efficiency	75%
Size / Dimension 4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.13" L x 1.91" W x 1.39" H (105.0mm x 48.5mm x 35.2mm)
		Report errors?

DTS120200UDC-P5P-TK Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS120200UDC-P5P-TK Payment Methods



















DTS120200UDC-P5P-TK Shipping Methods













If you have any question about DTS120200UDC-P5P-TK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com