



DTS120500UC-P5-ET Information



For Reference Only

Part Number DTS120500UC-P5-ET

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 60W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS120500UC-P5-ET Specifications

| Manufacturer Part Number DTS120500UC-P5-ET Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.76" L x 2.36" W x 1.36" H (121.0mm x 60.0mm x 34.5mm) | | |
|--|---------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Manufacturer Part Number | DTS120500UC-P5-ET |
| Package - Series - Region Utilized - Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Manufacturer | CUI Inc. |
| Package-Series-Region Utilized-FormDesktop (Class I)Input TypeCordVoltage - Input100 ~ 240 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency78%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Category | Power Supplies - External/Internal (Off-Board) |
| Series - Region Utilized - Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | | AC DC Desktop, Wall Adapters |
| Region Utilized - Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Package | - |
| Form Desktop (Class I) Input Type Cord Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Series | - |
| Input Type Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency 78% Operating Temperature O°C ~ 40°C Output Connector Cord 12V 60W No Load Power Consumption - Positive Center ITE (Commercial) 78% Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Region Utilized | - |
| Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $5A$ Power (Watts) $60W$ No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Form | Desktop (Class I) |
| Voltage - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Input Type | Cord |
| Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 78% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Voltage - Input | 100 ~ 240 VAC |
| Power (Watts) $60W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ | Voltage - Output | 12V |
| No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ | Current - Output (Max) | 5A |
| PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ | Power (Watts) | 60W |
| Applications ITE (Commercial) Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | No Load Power Consumption | - |
| Efficiency 78% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Polarization | Positive Center |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Applications | ITE (Commercial) |
| Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Efficiency | 78% |
| | Operating Temperature | 0°C ~ 40°C |
| Size / Dimension 4.76" L x 2.36" W x 1.36" H (121.0mm x 60.0mm x 34.5mm) | Output Connector | Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm |
| | Size / Dimension | 4.76" L x 2.36" W x 1.36" H (121.0mm x 60.0mm x 34.5mm) |
| Report errors? | | Report errors? |

DTS120500UC-P5-ET Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS120500UC-P5-ET Payment Methods



















DTS120500UC-P5-ET Shipping Methods













If you have any question about DTS120500UC-P5-ET, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com