

Heisener.com

DTS150133UDC-P5/RN

DTS150133UDC-P5/RN Information

Part Number DTS150133UDC-P5/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 15V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS150133UDC-P5/RN Specifications

Manufacturer Part Number DTS150133UDC-P5/RN Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS150133UDC-P5/RN
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized - Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33° L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Series	-
Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 1.33A Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 90 ~ 264 VAC 15V 10V 10V 10V 10V 10V 10V 10V	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 1.33A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max) 1.33A Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption Polarization Negative Center ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Output	15V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Ffficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	1.33A
Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0 \text{mm} \times 60.0 \text{mm} \times 34.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$	No Load Power Consumption	-
Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	70%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
		Report errors?

DTS150133UDC-P5/RN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS150133UDC-P5/RN Payment Methods



















DTS150133UDC-P5/RN Shipping Methods













If you have any question about DTS150133UDC-P5/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com