



### DTS240083UDC-P5P Information

Part Number DTS240083UDC-P5P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DTS240083UDC-P5P Specifications

Manufacturer Part Number         DTS240083UDC-P5P           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer Part Number	DTS240083UDC-P5P
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         100mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Package	-
Form Desktop (Class II)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 830mA  Power (Watts) 20W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Series	-
Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 830mA  Power (Watts) 20W  No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Region Utilized	-
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $830\text{mA}$ Power (Watts) $20\text{W}$ No Load Power Consumption $100\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency $70\%$ Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm}$ I.D. x $5.5\text{mm}$ O.D. x $12.0\text{mm}$ Size / Dimension $4.33$ " L x $2.36$ " W x $1.34$ " H ( $110.0\text{mm}$ x $60.0\text{mm}$ x $34.0\text{mm}$ )	Form	Desktop (Class II)
Voltage - Output Current - Output (Max)  830mA  Power (Watts)  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  24V  24V  24V  26V  26V  20W  100mW (Max)  Positive Center  100mW (Max)  Positive Center  100 C ~ 40° C  10° C ~ 40° C  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Input Type	Cord
Current - Output (Max)  Power (Watts)  20W  No Load Power Consumption  100mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $20W$ No Load Power Consumption $100mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)Efficiency $70\%$ Operating Temperature $10^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $2.1mm$ I.D. $x$ $5.5mm$ O.D. $x$ $12.0mm$ Size / Dimension $4.33$ " L $x$ $2.36$ " W $x$ $1.34$ " H ( $110.0mm$ $x$ $60.0mm$ $x$ $34.0mm$ )	Voltage - Output	24V
No Load Power Consumption 100mW (Max)  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Current - Output (Max)	830mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension $4.33'' \text{L} \times 2.36'' \text{W} \times 1.34'' \text{H} (110.0 \text{mm} \times 60.0 \text{mm} \times 34.0 \text{mm})$	Power (Watts)	20W
Applications ITE (Commercial)  Fificiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	No Load Power Consumption	100mW (Max)
Efficiency 70%   Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm   Size / Dimension $4.33^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.34^{\circ}\text{H} (110.0\text{mm} \times 60.0\text{mm} \times 34.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Efficiency	70%
Size / Dimension 4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	4.33" L x 2.36" W x 1.34" H (110.0mm x 60.0mm x 34.0mm)
		Report errors?

#### DTS240083UDC-P5P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DTS240083UDC-P5P Payment Methods



















# DTS240083UDC-P5P Shipping Methods













If you have any question about DTS240083UDC-P5P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com