

Heisener.com

DTS240083UDC-P9/RN

DTS240083UDC-P9/RN Information

Part Number DTS240083UDC-P9/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS240083UDC-P9/RN Specifications

Manufacturer DTS240083UDC-P9/RN Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Manufacturer Part Number	DTS240083UDC-P9/RN
AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 1000000000000000000000000000000000000	Manufacturer	CUI Inc.
Package-Series-Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)830mAPower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature10°C ~ 40°C	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C		AC DC Desktop, Wall Adapters
Region Utilized-FormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)830mAPower (Watts)20WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature10°C ~ 40°C	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Series	-
Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Input Type	Cord
Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Voltage - Input	90 ~ 264 VAC
Power (Watts) 20W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C	Voltage - Output	24V
No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Current - Output (Max)	830mA
Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$	No Load Power Consumption	-
Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Polarization	Negative Center
Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Applications	ITE (Commercial)
	Efficiency	70%
Output Compared D.	Operating Temperature	10°C ~ 40°C
Output Connector Barrel Plug R/A, 1.05mm 1.D. x 3.8mm O.D. x 9.5mm	Output Connector	Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm
Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Size / Dimension	3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)
Report errors?		Report errors?

DTS240083UDC-P9/RN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS240083UDC-P9/RN Payment Methods



















DTS240083UDC-P9/RN Shipping Methods













If you have any question about DTS240083UDC-P9/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com