

Heisener.com

## DTS240083UDC-P9/RP

#### DTS240083UDC-P9/RP Information

Part Number DTS240083UDC-P9/RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 24V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DTS240083UDC-P9/RP Specifications

Manufacturer Part Number         DTS240083UDC-P9/RP           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Manufacturer Part Number	DTS240083UDC-P9/RP
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         -           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         830mA           Power (Watts)         20W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)		AC DC Desktop, Wall Adapters
Region Utilized - Desktop (Class II)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 830mA  Power (Watts) 20W  No Load Power Consumption - Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Package	-
FormDesktop (Class II)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $830\text{mA}$ Power (Watts) $20\text{W}$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency $70\%$ Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $1.05\text{mm I.D. x } 3.8\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $3.54'' \text{ L x } 2.28'' \text{ W x } 1.10'' \text{ H } (90.0\text{mm x } 58.0\text{mm x } 28.0\text{mm})$	Series	-
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $24\text{V}$ Current - Output (Max) $830\text{mA}$ Power (Watts) $20\text{W}$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency $70\%$ Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, $1.05\text{mm}$ I.D. x $3.8\text{mm}$ O.D. x $9.5\text{mm}$ Size / Dimension $3.54^{\circ}$ L x $2.28^{\circ}$ W x $1.10^{\circ}$ H ( $90.0\text{mm}$ x $58.0\text{mm}$ x $28.0\text{mm}$ )	Region Utilized	-
Voltage - Input  90 ~ 264 VAC  Voltage - Output  24V  Current - Output (Max)  830mA  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension  90 ~ 264 VAC	Form	Desktop (Class II)
Voltage - Output  Current - Output (Max)  830mA  Power (Watts)  20W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension  3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Input Type	Cord
Current - Output (Max)  Power (Watts)  20W  No Load Power Consumption  - Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension  3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  20W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension  3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Voltage - Output	24V
No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension  3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Current - Output (Max)	830mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, $1.05\text{mm}$ I.D. x $3.8\text{mm}$ O.D. x $9.5\text{mm}$ Size / Dimension $3.54^{\circ}$ L x $2.28^{\circ}$ W x $1.10^{\circ}$ H ( $90.0\text{mm}$ x $58.0\text{mm}$ x $28.0\text{mm}$ )	Power (Watts)	20W
Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	No Load Power Consumption	-
Efficiency 70%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm  Size / Dimension $3.54^{\circ}\text{L} \times 2.28^{\circ} \text{W} \times 1.10^{\circ} \text{H} (90.0 \text{mm} \times 58.0 \text{mm} \times 28.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension $3.54^{\circ}\text{L x } 2.28^{\circ}\text{W x } 1.10^{\circ}\text{H } (90.0\text{mm x } 58.0\text{mm x } 28.0\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm           Size / Dimension         3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Efficiency	70%
Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 1.05mm I.D. x 3.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)
		Report errors?

#### DTS240083UDC-P9/RP Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DTS240083UDC-P9/RP Payment Methods



















## DTS240083UDC-P9/RP Shipping Methods













If you have any question about DTS240083UDC-P9/RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com