



DTS240083UDC-P9P Information

Heisener.com

Part Number DTS240083UDC-P9P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 20W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS240083UDC-P9P Specifications

Manufacturer Part Number DTS240083UDC-P9P Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Manufacturer Part Number	DTS240083UDC-P9P
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized - Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)		AC DC Desktop, Wall Adapters
Region Utilized - Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Series	-
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $1.05\text{mm I.D. x } 3.8\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $3.54^{\circ}\text{ L x } 2.28^{\circ}\text{ W x } 1.10^{\circ}\text{ H } (90.0\text{mm x } 58.0\text{mm x } 28.0\text{mm})$	Region Utilized	-
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 830mA Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 90 ~ 264 VAC 24V Current - Output (Max) 830mA Power (Watts)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Input Type	Cord
Current - Output (Max) 830mA Power (Watts) 20W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 20W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Voltage - Output	24V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Current - Output (Max)	830mA
Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Power (Watts)	20W
Applications ITE (Commercial) Efficiency 70% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension $3.54^{\circ}\text{L} \times 2.28^{\circ}\text{W} \times 1.10^{\circ}\text{H} (90.0\text{mm} \times 58.0\text{mm} \times 28.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Efficiency	70%
Size / Dimension 3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)	Operating Temperature	10°C ~ 40°C
·	Output Connector	Barrel Plug, 1.05mm I.D. x 3.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.54" L x 2.28" W x 1.10" H (90.0mm x 58.0mm x 28.0mm)
		Report errors?

DTS240083UDC-P9P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS240083UDC-P9P Payment Methods



















DTS240083UDC-P9P Shipping Methods













If you have any question about DTS240083UDC-P9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com