



DTS24F15-19PC Information

Heisener.com

Part Number DTS24F15-19PC

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 19POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS24F15-19PC Specifications

Manufacturer Part NumberDTS24F15-19PCManufacturerTE Connectivity Deutsch ConnectorsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert15-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 15-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Manufacturer Part Number	DTS24F15-19PC
Circular Connectors Package - Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 15-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Manufacturer	TE Connectivity Deutsch Connectors
Package - Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 15-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Category	Connectors, Interconnects
Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 19 Shell Size - Insert 15-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions19Shell Size - Insert15-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment Resistant	Package	-
Number of Positions19Shell Size - Insert15-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationCIngress ProtectionEnvironment Resistant	Series	MIL-DTL-38999 Series III, DTS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation C Ingress Protection Insert Inse	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Number of Positions	19
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Shell Size - Insert	15-19
Termination Crimp Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Shell Size, MIL	-
Fastening Type Threaded Orientation C Ingress Protection Environment Resistant	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation C Ingress Protection Environment Resistant	Termination	Crimp
Ingress Protection Environment Resistant	Fastening Type	Threaded
	Orientation	C
Shell Material, Finish Aluminum, Nickel Plated	Ingress Protection	Environment Resistant
	Shell Material, Finish	Aluminum, Nickel Plated
Contact Finish Gold	Contact Finish	Gold
Features Shielded	Features	Shielded
Voltage - Rated -	Voltage - Rated	-
Current Rating 7.5A	Current Rating	7.5A
Report errors?		Report errors?

DTS24F15-19PC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS24F15-19PC Payment Methods


































If you have any question about DTS24F15-19PC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com