



DTS24F25-4PE Information

Heisener.com

Part Number DTS24F25-4PE

Manufacturer TE Connectivity Deutsch Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 56POS JAM NUT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DTS24F25-4PE Specifications

| Manufacturer Part Number DTS24F25-4PE Manufacturer TE Connectivity Deutsch Connectors Category Connectors, Interconnects Package - Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | | |
|--|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7,5A, 13A | Manufacturer Part Number | DTS24F25-4PE |
| Package-SeriesMIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions56Shell Size - Insert25-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A | Manufacturer | TE Connectivity Deutsch Connectors |
| Package-SeriesMIL-DTL-38999 Series III, DTSConnector TypeReceptacle, Male PinsNumber of Positions56Shell Size - Insert25-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A | Category | Connectors, Interconnects |
| Series MIL-DTL-38999 Series III, DTS Connector Type Receptacle, Male Pins Number of Positions 56 Shell Size - Insert 25-4 Shell Size, MIL | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions56Shell Size - Insert25-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A | Package | - |
| Number of Positions56Shell Size - Insert25-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A | Series | MIL-DTL-38999 Series III, DTS |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Number of Positions | 56 |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationEIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating7.5A, 13A | Shell Size - Insert | 25-4 |
| Termination Crimp Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A | Shell Size, MIL | - |
| Fastening Type Threaded Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation E Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A, 13A | Orientation | E |
| Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Ingress Protection | Environment Resistant |
| Features Shielded Voltage - Rated - Current Rating 7.5A, 13A | Shell Material, Finish | Aluminum, Nickel Plated |
| Voltage - Rated - Current Rating 7.5A, 13A | Contact Finish | Gold |
| Current Rating 7.5A, 13A | Features | Shielded |
| | Voltage - Rated | - |
| Report errors? | Current Rating | 7.5A, 13A |
| | | Report errors? |

DTS24F25-4PE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS24F25-4PE Payment Methods



















DTS24F25-4PE Shipping Methods













If you have any question about DTS24F25-4PE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com