

DTS26F13-4PB

a Quote

DTS26F13-4PB Information

| Heisener.com | Part Number | DTS26F13-4PB | |
|--------------------|--------------|---|-----------|
| | Manufacturer | TE Connectivity Deutsch Connectors | 回答 |
| | Category | Connectors, Interconnects Circular Connectors | |
| | Description | CONN PLUG 4POS STRGHT W/PINS | |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DTS26F13-4PB Specifications

| TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Lurent Rating13A | | |
|---|--------------------------|------------------------------------|
| CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-38999 Series III, DTSConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionSulvironment ResistantShell Material, FinishGoldContact FinishSieleddVoltage - Rated-Voltage - Rated-StreatedSieleddStreated-Streated <td>Manufacturer Part Number</td> <td>DTS26F13-4PB</td> | Manufacturer Part Number | DTS26F13-4PB |
| Circular ConnectorsPackage-SeriesMIL-DTL-38999 Series III, DTSConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Manufacturer | TE Connectivity Deutsch Connectors |
| Package-SeriesMIL-DTL-3899 Series III, DTSConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeDireadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShelledaVoltage - RatedSheldedaVoltage - RatedShelledaStreadedShelledaShell Raterial FinishShelledaStreaded | Category | Connectors, Interconnects |
| SeriesMIL-DTL-38999 Series III, DTSConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeDreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShieldedVoltage - Rated. | | Circular Connectors |
| Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeHreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShieldedVoltage - Rated.Ingress ProtectionShieldedShieldedShieldedShieldedShieldedShielded.StatementShieldedShielded.StatementShieldedShielded.Statement. | Package | - |
| Number of Positions4Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShieldedFasturesShieldedVoltage - Rated13A | Series | MIL-DTL-38999 Series III, DTS |
| Shell Size - Insert13-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Connector Type | Plug, Male Pins |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Number of Positions | 4 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishGoldContact FinishShieldedYoltage - Rated-Yoltage - Rated13A | Shell Size - Insert | 13-4 |
| TerminationCrimpFastening TypeThreadedOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Lurent Rating13A | Shell Size, MIL | - |
| Fastening TypeThreadedFastening TypeBOrientationEnvironment ResistantIngress ProtectionAluminum, Nickel PlatedShell Material, FinishGoldContact FinishShieldedFeaturesShieldedVoltage - Rated-Current Rating13A | Mounting Type | Free Hanging (In-Line) |
| OrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Termination | Crimp |
| Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Fastening Type | Threaded |
| Shell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Orientation | В |
| Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating13A | Ingress Protection | Environment Resistant |
| FeaturesShieldedVoltage - Rated-Current Rating13A | Shell Material, Finish | Aluminum, Nickel Plated |
| Voltage - Rated-Current Rating13A | Contact Finish | Gold |
| Current Rating 13A | Features | Shielded |
| - | Voltage - Rated | - |
| Report errors? | Current Rating | 13A |
| | | Report errors? |

DTS26F13-4PB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DTS26F13-4PB Payment Methods





If you have any question about DTS26F13-4PB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com