



Heisener.com

For Reference Only

#### DW-08-14-L-S-200-LL Information

Part Number DW-08-14-L-S-200-LL

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DW-08-14-L-S-200-LL Specifications

Manufacturer Part Number         DW-08-14-L-S-200-LL           Manufacturer         Samtec Inc.           Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DW           Number of Positions         8           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         1.430" (36.32mm)           Length - Post (Mating)         1.120" (28.45mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DW  Number of Positions 8 Pitch 0.100" (2.54mm)  Number of Rows 1 Row Spacing Length - Overall Length - Post (Mating) 1.120" (28.45mm)  Length - Stack Height 0.200" (5.08mm)  Length - Tail Mounting Type Termination Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Manufacturer Part Number	DW-08-14-L-S-200-LL
Rectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions8Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall1.430" (36.32mm)Length - Post (Mating)1.120" (28.45mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DW           Number of Positions         8           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         1.430" (36.32mm)           Length - Post (Mating)         1.120" (28.45mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)	Category	Connectors, Interconnects
Series         Flex Stack, DW           Number of Positions         8           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         1.430" (36.32mm)           Length - Post (Mating)         1.120" (28.45mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions       8         Pitch       0.100" (2.54mm)         Number of Rows       1         Row Spacing       -         Length - Overall       1.430" (36.32mm)         Length - Post (Mating)       1.120" (28.45mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Package	-
Pitch       0.100" (2.54mm)         Number of Rows       1         Row Spacing       -         Length - Overall       1.430" (36.32mm)         Length - Post (Mating)       1.120" (28.45mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Series	Flex Stack, DW
Number of Rows       1         Row Spacing       -         Length - Overall       1.430" (36.32mm)         Length - Post (Mating)       1.120" (28.45mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Number of Positions	8
Row Spacing       -         Length - Overall       1.430" (36.32mm)         Length - Post (Mating)       1.120" (28.45mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Pitch	0.100" (2.54mm)
Length - Overall       1.430" (36.32mm)         Length - Post (Mating)       1.120" (28.45mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Number of Rows	1
Length - Post (Mating)1.120" (28.45mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Row Spacing	-
Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Overall	1.430" (36.32mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Post (Mating)	1.120" (28.45mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Stack Height	0.200" (5.08mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
DI I	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Color Black	Color	Black
Report errors?		Report errors?

### DW-08-14-L-S-200-LL Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DW-08-14-L-S-200-LL Payment Methods



















## DW-08-14-L-S-200-LL Shipping Methods













If you have any question about DW-08-14-L-S-200-LL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com