

### DW-10-13-S-T-965 Information

Heisener.com

For Reference Only

Part Number DW-10-13-S-T-965

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-10-13-S-T-965 Specifications

Manufacturer Part NumberDW-10-13-S-T-965ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions30Pitch0.100" (2.54mm)Number of Rows3Row Spacing0.100" (2.54mm)Length - Overall1.230" (31.24mm)Length - Post (Mating)0.155" (3.94mm)Length - Stack Height0.965" (24.51mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)ColorBlack		
Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DW           Number of Positions         30           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.230" (31.24mm)           Length - Post (Mating)         0.155" (3.94mm)           Length - Stack Height         0.965" (24.51mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30µin (0.76µm)	Manufacturer Part Number	DW-10-13-S-T-965
Package-SeriesFlex Stack, DWNumber of Positions30Pitch0.100" (2.54mm)Number of Rows3Row Spacing0.100" (2.54mm)Length - Overall1.230" (31.24mm)Length - Post (Mating)0.155" (3.94mm)Length - Stack Height0.965" (24.51mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DW           Number of Positions         30           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.230" (31.24mm)           Length - Post (Mating)         0.155" (3.94mm)           Length - Stack Height         0.965" (24.51mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30µin (0.76µm)	Category	Connectors, Interconnects
Series         Flex Stack, DW           Number of Positions         30           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.230" (31.24mm)           Length - Post (Mating)         0.155" (3.94mm)           Length - Stack Height         0.965" (24.51mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30μin (0.76μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions       30         Pitch       0.100" (2.54mm)         Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.230" (31.24mm)         Length - Post (Mating)       0.155" (3.94mm)         Length - Stack Height       0.965" (24.51mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Package	-
Pitch       0.100" (2.54mm)         Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.230" (31.24mm)         Length - Post (Mating)       0.155" (3.94mm)         Length - Stack Height       0.965" (24.51mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Series	Flex Stack, DW
Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.230" (31.24mm)         Length - Post (Mating)       0.155" (3.94mm)         Length - Stack Height       0.965" (24.51mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Number of Positions	30
Row Spacing       0.100" (2.54mm)         Length - Overall       1.230" (31.24mm)         Length - Post (Mating)       0.155" (3.94mm)         Length - Stack Height       0.965" (24.51mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Pitch	0.100" (2.54mm)
Length - Overall       1.230" (31.24mm)         Length - Post (Mating)       0.155" (3.94mm)         Length - Stack Height       0.965" (24.51mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Number of Rows	3
Length - Post (Mating)0.155" (3.94mm)Length - Stack Height0.965" (24.51mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.965" (24.51mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Overall	1.230" (31.24mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Post (Mating)	0.155" (3.94mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Stack Height	0.965" (24.51mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	30μin (0.76μm)
	Color	Black
Report errors?		Report errors?

#### DW-10-13-S-T-965 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DW-10-13-S-T-965 Payment Methods



















## DW-10-13-S-T-965 Shipping Methods













If you have any question about DW-10-13-S-T-965, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com