

### DW-17-20-G-D-845 Information

Heisener.com

For Reference Only

Part Number DW-17-20-G-D-845

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-17-20-G-D-845 Specifications

Manufacturer Part NumberDW-17-20-G-D-845ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions34Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.130" (28.70mm)Length - Post (Mating)0.175" (4.45mm)Length - Stack Height0.845" (21.46mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DW  Number of Positions 34  Pitch 0.100" (2.54mm)  Number of Rows 2  Row Spacing 0.100" (2.54mm)  Length - Overall 1.130" (28.70mm)  Length - Post (Mating) 0.175" (4.45mm)  Length - Stack Height 0.845" (21.46mm)  Length - Tail 0.110" (2.79mm)  Mounting Type Through Hole Termination Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Manufacturer Part Number	DW-17-20-G-D-845
Package-SeriesFlex Stack, DWNumber of Positions34Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.130" (28.70mm)Length - Post (Mating)0.175" (4.45mm)Length - Stack Height0.845" (21.46mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DW           Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         1.130" (28.70mm)           Length - Post (Mating)         0.175" (4.45mm)           Length - Stack Height         0.845" (21.46mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)	Category	Connectors, Interconnects
Series         Flex Stack, DW           Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         1.130" (28.70mm)           Length - Post (Mating)         0.175" (4.45mm)           Length - Stack Height         0.845" (21.46mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions       34         Pitch       0.100" (2.54mm)         Number of Rows       2         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.175" (4.45mm)         Length - Stack Height       0.845" (21.46mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Package	-
Pitch       0.100" (2.54mm)         Number of Rows       2         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.175" (4.45mm)         Length - Stack Height       0.845" (21.46mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Series	Flex Stack, DW
Number of Rows       2         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.175" (4.45mm)         Length - Stack Height       0.845" (21.46mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Number of Positions	34
Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.175" (4.45mm)         Length - Stack Height       0.845" (21.46mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Pitch	0.100" (2.54mm)
Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.175" (4.45mm)         Length - Stack Height       0.845" (21.46mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)	Number of Rows	2
Length - Post (Mating)0.175" (4.45mm)Length - Stack Height0.845" (21.46mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.845" (21.46mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Overall	1.130" (28.70mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Post (Mating)	0.175" (4.45mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Stack Height	0.845" (21.46mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
	Color	Black
Report errors?		Report errors?

#### DW-17-20-G-D-845 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DW-17-20-G-D-845 Payment Methods



















## DW-17-20-G-D-845 Shipping Methods













If you have any question about DW-17-20-G-D-845, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com