

DW-30-12-G-D-676

DW-30-12-G-D-676 Information

Heisener.com	Part Number Manufacturer Category Description Package	DW-30-12-G-D-676 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) .025" BOARD SPACERS	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DW-30-12-G-D-676 Specifications

Manufacturer Part NumberDW-30-12-G-D-676ManufacturerSantec Inc.CategoryConnectors, InterconnectsPackage-SeriesFlex Stack, DWNumber of Positions60Pitch0.100° (2.54mm)Number of Rows2Row Spacing0.00° (2.54mm)Length - Overall0.30° (26.16mm)Length - Stack Height0.676° (17.17mm)Length - Tail0.676° (17.17mm)Mounting TypeSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)GoldContact Finish Thickness - Post (Mating)GoldContact Finish Thickness - Post (Mating)Black		
CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldLongth - Fost (Mating)10µin (0.25µm)	facturer Part Number	DW-30-12-G-D-676
Number of PositionsRectangular Connectors - Board Spacers, Stackers (Board to Board)Number of PositionsFlex Stack, DWNumber of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldLongth - Tisish Thickness - Post (Mating)10µin (0.25µm)	facturer S	Samtec Inc.
Package-SeriesFlex Stack, DWNumber of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)0.941Dot State Finish Thickness - Post (Mating)0.941Other State Finish Thickness - Post (Mating)0.941Descent Finish Thickness - Post (Mating)0.941State Finish Thickness - Post (Mating)0.941Descent Finish Thickness - Post (Mating)0.941Descent Finish - Post (Mating F	ory C	Connectors, Interconnects
SeriesFlex Stack, DWNumber of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Iopin (0.25µm)Contact Finish Thickness - Post (Mating)Iopin (0.25µm)	F	Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldKontact Finish - Post (Mating)Ipin (0.25µm)	ige -	-
Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish - Post (Mating)10µin (0.25µm)	s F	Flex Stack, DW
Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	ber of Positions 6	60
Row Spacing 0.100" (2.54mm) Length - Overall 1.030" (26.16mm) Length - Post (Mating) 0.244" (6.20mm) Length - Stack Height 0.676" (17.17mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Yount (See See See See See See See See See Se	С	0.100" (2.54mm)
Length - Overall1.030" (26.16mm)Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	per of Rows 2	2
Length - Post (Mating)0.244" (6.20mm)Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	Spacing C	0.100" (2.54mm)
Length - Stack Height0.676" (17.17mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	h - Overall 1	1.030" (26.16mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	h - Post (Mating)	0.244" (6.20mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	h - Stack Height 0	0.676" (17.17mm)
TerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	h - Tail C	0.110" (2.79mm)
Contact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)	iting Type 7	Through Hole
Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	ination S	Solder
	ct Finish - Post (Mating)	Gold
Color Black	ct Finish Thickness - Post (Mating) 1	10µin (0.25µm)
	F	Black
Repor		Report errors?

DW-30-12-G-D-676 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DW-30-12-G-D-676 Payment Methods



DW-30-12-G-D-676 Shipping Methods



If you have any question about DW-30-12-G-D-676, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com