

### DW-30-16-G-D-200 Information

Heisener.com

For Reference Only

Part Number DW-30-16-G-D-200

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-30-16-G-D-200 Specifications

| Manufacturer Part NumberDW-30-16-G-D-200ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions60Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.445" (11.30mm)Length - Post (Mating)0.135" (3.43mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10µin (0.25µm)                                   |  |   |
|--|--|---|
| Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DW Number of Positions 60 Pitch 0.100" (2.54mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.445" (11.30mm) Length - Post (Mating) 0.135" (3.43mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold   | Manufacturer Part Number                 | DW-30-16-G-D-200  |
| Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DW  Number of Positions 60  Pitch 0.100" (2.54mm)  Number of Rows 2  Row Spacing 0.100" (2.54mm)  Length - Overall 0.445" (11.30mm)  Length - Post (Mating) 0.135" (3.43mm)  Length - Stack Height 0.200" (5.08mm)  Length - Tail 0.110" (2.79mm)  Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Gold   | Manufacturer                             | Samtec Inc.   |
| Package         -           Series         Flex Stack, DW           Number of Positions         60           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.445" (11.30mm)           Length - Post (Mating)         0.135" (3.43mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold | Category                                 | Connectors, Interconnects   |
| Series         Flex Stack, DW           Number of Positions         60           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.445" (11.30mm)           Length - Post (Mating)         0.135" (3.43mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold                             |  | Rectangular Connectors - Board Spacers, Stackers (Board to Board) |
| Number of Positions         60           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.445" (11.30mm)           Length - Post (Mating)         0.135" (3.43mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold   | Package                                  | -   |
| Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.445" (11.30mm)           Length - Post (Mating)         0.135" (3.43mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold  | Series                                   | Flex Stack, DW  |
| Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.445" (11.30mm)           Length - Post (Mating)         0.135" (3.43mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold  | Number of Positions                      | 60  |
| Row Spacing       0.100" (2.54mm)         Length - Overall       0.445" (11.30mm)         Length - Post (Mating)       0.135" (3.43mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold   | Pitch                                    | 0.100" (2.54mm)   |
| Length - Overall       0.445" (11.30mm)         Length - Post (Mating)       0.135" (3.43mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold   | Number of Rows                           | 2   |
| Length - Post (Mating)       0.135" (3.43mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold   | Row Spacing                              | 0.100" (2.54mm)   |
| Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold   | Length - Overall                         | 0.445" (11.30mm)  |
| Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold   | Length - Post (Mating)                   | 0.135" (3.43mm)   |
| Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Gold  | Length - Stack Height                    | 0.200" (5.08mm)   |
| Termination Solder Contact Finish - Post (Mating) Gold   | Length - Tail                            | 0.110" (2.79mm)   |
| Contact Finish - Post (Mating) Gold  | Mounting Type                            | Through Hole  |
| -  | Termination                              | Solder  |
| Contact Finish Thickness - Post (Mating) 10μin (0.25μm)  | Contact Finish - Post (Mating)           | Gold  |
|  | Contact Finish Thickness - Post (Mating) | 10μin (0.25μm)  |
| Color Black  | Color                                    | Black   |
| Report errors?   |  | Report errors?  |

#### DW-30-16-G-D-200 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DW-30-16-G-D-200 Payment Methods



















# DW-30-16-G-D-200 Shipping Methods













If you have any question about DW-30-16-G-D-200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com