

DW-30-20-F-S-810 Information

Heisener.com

For Reference Only

Part Number DW-30-20-F-S-810

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

Description .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DW-30-20-F-S-810 Specifications

Manufacturer Part Number DW-30-20-F-S-810 Manufacturer Samtec Inc. Category Connectors, Interconnects Package - Series Flex Stack, DW Number of Positions 30 Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm) Color Black		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DW Number of Positions 30 Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Manufacturer Part Number	DW-30-20-F-S-810
Package-SeriesFlex Stack, DWNumber of Positions30Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall1.130" (28.70mm)Length - Post (Mating)0.210" (5.34mm)Length - Stack Height0.810" (20.57mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)3µin (0.08µm)	Manufacturer	Samtec Inc.
Package - Series Flex Stack, DW Number of Positions 30 Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3µin (0.08μm)	Category	Connectors, Interconnects
Series Flex Stack, DW Number of Positions 30 Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions 30 Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Package	-
Pitch 0.100" (2.54mm) Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Series	Flex Stack, DW
Number of Rows 1 Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Number of Positions	30
Row Spacing - Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Pitch	0.100" (2.54mm)
Length - Overall 1.130" (28.70mm) Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Number of Rows	1
Length - Post (Mating) 0.210" (5.34mm) Length - Stack Height 0.810" (20.57mm) Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Row Spacing	-
Length - Stack Height0.810" (20.57mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)3μin (0.08μm)	Length - Overall	1.130" (28.70mm)
Length - Tail 0.110" (2.79mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3µin (0.08µm)	Length - Post (Mating)	0.210" (5.34mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)3μin (0.08μm)	Length - Stack Height	0.810" (20.57mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 3μin (0.08μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	3μin (0.08μm)
	Color	Black
Report errors?		Report errors?

DW-30-20-F-S-810 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DW-30-20-F-S-810 Payment Methods



















DW-30-20-F-S-810 Shipping Methods













If you have any question about DW-30-20-F-S-810, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com