

### DW-34-08-G-S-200 Information

Heisener.com

For Reference Only

Part Number DW-34-08-G-S-200

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-34-08-G-S-200 Specifications

Manufacturer Part NumberDW-34-08-G-S-200ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions34Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.530" (13.46mm)Length - Post (Mating)0.220" (5.59mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack		
CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions34Pitch0.100" (2.54mm)Number of Rows1Row Spacing-Length - Overall0.530" (13.46mm)Length - Post (Mating)0.220" (5.59mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Manufacturer Part Number	DW-34-08-G-S-200
Package         -           Series         Flex Stack, DW           Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DW           Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Category	Connectors, Interconnects
Series         Flex Stack, DW           Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         34           Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Package	-
Pitch         0.100" (2.54mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Series	Flex Stack, DW
Number of Rows         1           Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Number of Positions	34
Row Spacing         -           Length - Overall         0.530" (13.46mm)           Length - Post (Mating)         0.220" (5.59mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Pitch	0.100" (2.54mm)
Length - Overall       0.530" (13.46mm)         Length - Post (Mating)       0.220" (5.59mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)         Color       Black	Number of Rows	1
Length - Post (Mating)0.220" (5.59mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Row Spacing	-
Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Overall	0.530" (13.46mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Post (Mating)	0.220" (5.59mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Stack Height	0.200" (5.08mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Termination	Solder
Color Black	Contact Finish - Post (Mating)	Gold
	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Report errors?	Color	Black
		Report errors?

#### DW-34-08-G-S-200 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DW-34-08-G-S-200 Payment Methods





















## DW-34-08-G-S-200 Shipping Methods













If you have any question about DW-34-08-G-S-200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com