



Heisener.com

For Reference Only

### DW-40-10-G-D-430-LL Information

Part Number DW-40-10-G-D-430-LL

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-40-10-G-D-430-LL Specifications

Manufacturer Part NumberDW-40-10-G-D-430-LLManufacturerSamtec Inc.CategoryConnectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWNumber of Positions80Pitch0.100" (2.54mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.830" (21.08mm)Length - Post (Mating)0.290" (7.37mm)Length - Stack Height0.430" (10.92mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack		
Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DW           Number of Positions         80           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         I0µin (0.25µm)           Color         Black	Manufacturer Part Number	DW-40-10-G-D-430-LL
Package         -           Series         Flex Stack, DW           Number of Positions         80           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DW           Number of Positions         80           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Category	Connectors, Interconnects
Series         Flex Stack, DW           Number of Positions         80           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         80           Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Package	-
Pitch         0.100" (2.54mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Series	Flex Stack, DW
Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.830" (21.08mm)           Length - Post (Mating)         0.290" (7.37mm)           Length - Stack Height         0.430" (10.92mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Number of Positions	80
Row Spacing       0.100" (2.54mm)         Length - Overall       0.830" (21.08mm)         Length - Post (Mating)       0.290" (7.37mm)         Length - Stack Height       0.430" (10.92mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)         Color       Black	Pitch	0.100" (2.54mm)
Length - Overall       0.830" (21.08mm)         Length - Post (Mating)       0.290" (7.37mm)         Length - Stack Height       0.430" (10.92mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)         Color       Black	Number of Rows	2
Length - Post (Mating)0.290" (7.37mm)Length - Stack Height0.430" (10.92mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.430" (10.92mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Overall	0.830" (21.08mm)
Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Post (Mating)	0.290" (7.37mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Stack Height	0.430" (10.92mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Length - Tail	0.110" (2.79mm)
Contact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Termination	Solder
Color Black	Contact Finish - Post (Mating)	Gold
	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Report errors?	Color	Black
		Report errors?

### DW-40-10-G-D-430-LL Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DW-40-10-G-D-430-LL Payment Methods





















## DW-40-10-G-D-430-LL Shipping Methods













If you have any question about DW-40-10-G-D-430-LL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com