

#### DW-40-20-S-T-200 Information

Heisener.com

For Reference Only

Part Number DW-40-20-S-T-200

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .025" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DW-40-20-S-T-200 Specifications

| Manufacturer Part Number  Manufacturer  Samtec Inc.  Category  Connectors, Interconnects  Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package  Series  Flex Stack, DW  Number of Positions  120  Pitch  0.100" (2.54mm)  Number of Rows  3  Row Spacing  0.100" (2.54mm)  Length - Overall  1.130" (28.70mm)  Length - Post (Mating)  Length - Stack Height  0.200" (5.08mm)  Length - Tail  0.110" (2.79mm)  Mounting Type  Through Hole  Termination  Solder  Contact Finish - Post (Mating)  Gold   |  |   |
|---|--|---|
| Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DW           Number of Positions         120           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.130" (28.70mm)           Length - Post (Mating)         0.820" (20.83mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder | Manufacturer Part Number                 | DW-40-20-S-T-200  |
| Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DW  Number of Positions 120  Pitch 0.100" (2.54mm)  Number of Rows 3  Row Spacing 0.100" (2.54mm)  Length - Overall 1.130" (28.70mm)  Length - Post (Mating) 0.820" (20.83mm)  Length - Stack Height 0.200" (5.08mm)  Length - Tail 0.110" (2.79mm)  Mounting Type Through Hole  Termination Solder   | Manufacturer                             | Samtec Inc.   |
| Package         -           Series         Flex Stack, DW           Number of Positions         120           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.130" (28.70mm)           Length - Post (Mating)         0.820" (20.83mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder  | Category                                 | Connectors, Interconnects   |
| Series         Flex Stack, DW           Number of Positions         120           Pitch         0.100" (2.54mm)           Number of Rows         3           Row Spacing         0.100" (2.54mm)           Length - Overall         1.130" (28.70mm)           Length - Post (Mating)         0.820" (20.83mm)           Length - Stack Height         0.200" (5.08mm)           Length - Tail         0.110" (2.79mm)           Mounting Type         Through Hole           Termination         Solder  |  | Rectangular Connectors - Board Spacers, Stackers (Board to Board) |
| Number of Positions       120         Pitch       0.100" (2.54mm)         Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.820" (20.83mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder  | Package                                  | -   |
| Pitch       0.100" (2.54mm)         Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.820" (20.83mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder  | Series                                   | Flex Stack, DW  |
| Number of Rows       3         Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.820" (20.83mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder  | Number of Positions                      | 120   |
| Row Spacing       0.100" (2.54mm)         Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.820" (20.83mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder   | Pitch                                    | 0.100" (2.54mm)   |
| Length - Overall       1.130" (28.70mm)         Length - Post (Mating)       0.820" (20.83mm)         Length - Stack Height       0.200" (5.08mm)         Length - Tail       0.110" (2.79mm)         Mounting Type       Through Hole         Termination       Solder   | Number of Rows                           | 3   |
| Length - Post (Mating)0.820" (20.83mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolder  | Row Spacing                              | 0.100" (2.54mm)   |
| Length - Stack Height0.200" (5.08mm)Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolder  | Length - Overall                         | 1.130" (28.70mm)  |
| Length - Tail0.110" (2.79mm)Mounting TypeThrough HoleTerminationSolder  | Length - Post (Mating)                   | 0.820" (20.83mm)  |
| Mounting Type Through Hole Termination Solder   | Length - Stack Height                    | 0.200" (5.08mm)   |
| Termination Solder  | Length - Tail                            | 0.110" (2.79mm)   |
|   | Mounting Type                            | Through Hole  |
| Contact Finish - Post (Mating) Gold   | Termination                              | Solder  |
| Contact I mish 1 ost (Matting)  | Contact Finish - Post (Mating)           | Gold  |
| Contact Finish Thickness - Post (Mating) 30μin (0.76μm)   | Contact Finish Thickness - Post (Mating) | 30μin (0.76μm)  |
| Color Black   | Color                                    | Black   |
| Report errors?  |  | Report errors?  |

#### DW-40-20-S-T-200 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DW-40-20-S-T-200 Payment Methods



















## DW-40-20-S-T-200 Shipping Methods













If you have any question about DW-40-20-S-T-200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com