

### DWM-18-60-S-S-250 Information

Heisener.com

For Reference Only

Part Number DWM-18-60-S-S-250

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DWM-18-60-S-S-250 Specifications

Manufacturer Part NumberDWM-18-60-S-S-250ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWMNumber of Positions18Pitch0.050" (1.27mm)Number of Rows1Row Spacing-Length - Overall0.825" (20.96mm)Length - Post (Mating)0.455" (11.57mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)ColorBlack		
Category Canectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DWM  Number of Positions 18 Pitch 0.050" (1.27mm)  Number of Rows 1 Row Spacing - Length - Overall Length - Post (Mating) Length - Stack Height 0.250" (6.35mm)  Length - Tail Mounting Type Termination Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 30µin (0.76µm)	Manufacturer Part Number	DWM-18-60-S-S-250
Package-SeriesFlex Stack, DWMNumber of Positions18Pitch0.050" (1.27mm)Number of Rows1Row Spacing-Length - Overall0.825" (20.96mm)Length - Post (Mating)0.455" (11.57mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DWM           Number of Positions         18           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.825" (20.96mm)           Length - Post (Mating)         0.455" (11.57mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30µin (0.76µm)	Category	Connectors, Interconnects
Series         Flex Stack, DWM           Number of Positions         18           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.825" (20.96mm)           Length - Post (Mating)         0.455" (11.57mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30μin (0.76μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions       18         Pitch       0.050" (1.27mm)         Number of Rows       1         Row Spacing       -         Length - Overall       0.825" (20.96mm)         Length - Post (Mating)       0.455" (11.57mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Package	-
Pitch       0.050" (1.27mm)         Number of Rows       1         Row Spacing       -         Length - Overall       0.825" (20.96mm)         Length - Post (Mating)       0.455" (11.57mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Series	Flex Stack, DWM
Number of Rows       1         Row Spacing       -         Length - Overall       0.825" (20.96mm)         Length - Post (Mating)       0.455" (11.57mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Number of Positions	18
Row Spacing       -         Length - Overall       0.825" (20.96mm)         Length - Post (Mating)       0.455" (11.57mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Pitch	0.050" (1.27mm)
Length - Overall0.825" (20.96mm)Length - Post (Mating)0.455" (11.57mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Number of Rows	1
Length - Post (Mating)       0.455" (11.57mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Row Spacing	-
Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Overall	0.825" (20.96mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Post (Mating)	0.455" (11.57mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Stack Height	0.250" (6.35mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating)  Contact Finish Thickness - Post (Mating)  30μin (0.76μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 30µin (0.76µm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	30μin (0.76μm)
Color	Color	Black
Report errors?		Report errors?

#### DWM-18-60-S-S-250 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DWM-18-60-S-S-250 Payment Methods


































If you have any question about DWM-18-60-S-S-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com