



#### DWM-19-52-T-D-250 Information

Heisener.com

For Reference Only

Part Number DWM-19-52-T-D-250

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .050" BOARD SPACERS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DWM-19-52-T-D-250 Specifications

Manufacturer Part NumberDWM-19-52-T-D-250ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWMNumber of Positions38Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.425" (10.80mm)Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)TinContact Finish Thickness - Post (Mating)-ColorBlack		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DWM  Number of Positions 38 Pitch 0.050" (1.27mm)  Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm)  Mounting Type Through Hole Termination Contact Finish - Post (Mating) Tin Contact Finish Thickness - Post (Mating) Color Black	Manufacturer Part Number	DWM-19-52-T-D-250
Package-SeriesFlex Stack, DWMNumber of Positions38Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.425" (10.80mm)Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)-Contact Finish Thickness - Post (Mating)-ColorBlack	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DWM           Number of Positions         38           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Tin           Contact Finish Thickness - Post (Mating)         -           Color         Black	Category	Connectors, Interconnects
Series         Flex Stack, DWM           Number of Positions         38           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Tin           Contact Finish Thickness - Post (Mating)         -           Color         Black		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         38           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Tin           Contact Finish Thickness - Post (Mating)         -           Color         Black	Package	-
Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Tin           Contact Finish Thickness - Post (Mating)         -           Color         Black	Series	Flex Stack, DWM
Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Tin           Contact Finish Thickness - Post (Mating)         -           Color         Black	Number of Positions	38
Row Spacing       0.100" (2.54mm)         Length - Overall       0.425" (10.80mm)         Length - Post (Mating)       0.055" (1.40mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Tin         Contact Finish Thickness - Post (Mating)       -         Color       Black	Pitch	0.050" (1.27mm)
Length - Overall  Length - Post (Mating)  Length - Stack Height  O.250" (6.35mm)  Length - Tail  O.120" (3.05mm)  Mounting Type  Through Hole  Termination  Contact Finish - Post (Mating)  Contact Finish Thickness - Post (Mating)  Color  Black	Number of Rows	2
Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)TinContact Finish Thickness - Post (Mating)-ColorBlack	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)TinContact Finish Thickness - Post (Mating)-ColorBlack	Length - Overall	0.425" (10.80mm)
Length - Tail 0.120" (3.05mm)  Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Tin  Contact Finish Thickness - Post (Mating) -  Color Black	Length - Post (Mating)	0.055" (1.40mm)
Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Tin  Contact Finish Thickness - Post (Mating) -  Color Black	Length - Stack Height	0.250" (6.35mm)
Termination Solder Contact Finish - Post (Mating) Tin Contact Finish Thickness - Post (Mating) - Color Black	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating)  Contact Finish Thickness - Post (Mating)  Color  Black	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating)  Color Black	Termination	Solder
Color Black	Contact Finish - Post (Mating)	Tin
	Contact Finish Thickness - Post (Mating)	-
Report errors?	Color	Black
Report cross.		Report errors?

### DWM-19-52-T-D-250 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DWM-19-52-T-D-250 Payment Methods



















# DWM-19-52-T-D-250 Shipping Methods













If you have any question about DWM-19-52-T-D-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com