

### DWM-29-57-L-S-250 Information

Heisener.com

For Reference Only

Part Number DWM-29-57-L-S-250

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DWM-29-57-L-S-250 Specifications

Manufacturer Part Number  Manufacturer  Samtec Inc.  Category  Connectors, Interconnects  Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package  Series  Flex Stack, DWM  Number of Positions  29  Pitch  0.050" (1.27mm)  Number of Rows  1  Row Spacing  Length - Overall  Length - Post (Mating)  Length - Tail  Mounting Type  Through Hole  Termination  Contact Finish - Post (Mating)  Gold  Gold  Contact Finish - Post (Mating)  Gold  Contact Finish - Post (Mating)  Gold  Gold  Contact Finish - Post (Mating)  Gold  Contact Finish - Post (Mating)  Gold  Gold  Contact Finish - Post (Mating)  Gold  Contact Finish - Post (Mating)		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DWM Number of Positions 29 Pitch 0.050" (1.27mm)  Number of Rows 1 Row Spacing - Length - Overall 0.650" (16.50mm) Length - Post (Mating) 0.280" (7.12mm)  Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm)  Mounting Type Through Hole Termination Solder  Contact Finish - Post (Mating) Gold	Manufacturer Part Number	DWM-29-57-L-S-250
Rectangular Connectors - Board Spacers, Stackers (Board to Board)  Package - Series Flex Stack, DWM  Number of Positions 29  Pitch 0.050" (1.27mm)  Number of Rows 1  Row Spacing - Length - Overall 0.650" (16.50mm)  Length - Post (Mating) 0.280" (7.12mm)  Length - Stack Height 0.250" (6.35mm)  Length - Tail 0.120" (3.05mm)  Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Gold	Manufacturer	Samtec Inc.
Package Series Flex Stack, DWM Number of Positions 29 Pitch 0.050" (1.27mm) Number of Rows 1 Row Spacing - Length - Overall 0.650" (16.50mm) Length - Post (Mating) 0.280" (7.12mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Contact Finish - Post (Mating) Gold	Category	Connectors, Interconnects
Series         Flex Stack, DWM           Number of Positions         29           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.650" (16.50mm)           Length - Post (Mating)         0.280" (7.12mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         29           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.650" (16.50mm)           Length - Post (Mating)         0.280" (7.12mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold	Package	-
Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.650" (16.50mm)           Length - Post (Mating)         0.280" (7.12mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold	Series	Flex Stack, DWM
Number of Rows       1         Row Spacing       -         Length - Overall       0.650" (16.50mm)         Length - Post (Mating)       0.280" (7.12mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold	Number of Positions	29
Row Spacing         -           Length - Overall         0.650" (16.50mm)           Length - Post (Mating)         0.280" (7.12mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold	Pitch	0.050" (1.27mm)
Length - Overall       0.650" (16.50mm)         Length - Post (Mating)       0.280" (7.12mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold	Number of Rows	1
Length - Post (Mating)       0.280" (7.12mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold	Row Spacing	-
Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold	Length - Overall	0.650" (16.50mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold	Length - Post (Mating)	0.280" (7.12mm)
Mounting Type Through Hole  Termination Solder  Contact Finish - Post (Mating) Gold	Length - Stack Height	0.250" (6.35mm)
Termination Solder Contact Finish - Post (Mating) Gold	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating)  Gold	Mounting Type	Through Hole
-	Termination	Solder
C + (F' 1 FI 1 P + (A.C.)	Contact Finish - Post (Mating)	Gold
Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Color Black	Color	Black
Report errors?		Report errors?

### DWM-29-57-L-S-250 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DWM-29-57-L-S-250 Payment Methods





















## DWM-29-57-L-S-250 Shipping Methods













If you have any question about DWM-29-57-L-S-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com