

### DWM-32-01-G-D-330 Information

Heisener.com

For Reference Only

Part Number DWM-32-01-G-D-330

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DWM-32-01-G-D-330 Specifications

Manufacturer Part Number     DWM-32-01-G-D-330       Manufacturer     Samtec Inc.       Category     Connectors, Interconnects       Rectangular Connectors - Board Spacers, Stackers (Board to Board)       Package     -       Series     Flex Stack, DWM       Number of Positions     64       Pitch     0.050" (1.27mm)       Number of Rows     2       Row Spacing     0.100" (2.54mm)       Length - Overall     0.450" (11.43mm)       Length - Post (Mating)     -       Length - Stack Height     0.330" (8.38mm)       Length - Tail     0.120" (3.05mm)       Mounting Type     Through Hole       Termination     Solder       Contact Finish - Post (Mating)     Gold       Contact Finish Thickness - Post (Mating)     10µin (0.25µm)       Color     Black		
Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DWM           Number of Positions         64           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Manufacturer Part Number	DWM-32-01-G-D-330
Rectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWMNumber of Positions64Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.450" (11.43mm)Length - Post (Mating)-Length - Stack Height0.330" (8.38mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DWM           Number of Positions         64           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Category	Connectors, Interconnects
Series         Flex Stack, DWM           Number of Positions         64           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         64           Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Package	-
Pitch         0.050" (1.27mm)           Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Series	Flex Stack, DWM
Number of Rows         2           Row Spacing         0.100" (2.54mm)           Length - Overall         0.450" (11.43mm)           Length - Post (Mating)         -           Length - Stack Height         0.330" (8.38mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         10μin (0.25μm)           Color         Black	Number of Positions	64
Row Spacing       0.100" (2.54mm)         Length - Overall       0.450" (11.43mm)         Length - Post (Mating)       -         Length - Stack Height       0.330" (8.38mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)         Color       Black	Pitch	0.050" (1.27mm)
Length - Overall       0.450" (11.43mm)         Length - Post (Mating)       -         Length - Stack Height       0.330" (8.38mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       10μin (0.25μm)         Color       Black	Number of Rows	2
Length - Post (Mating)-Length - Stack Height0.330" (8.38mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.330" (8.38mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Overall	0.450" (11.43mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Post (Mating)	-
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Length - Stack Height	0.330" (8.38mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)ColorBlack	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black	Termination	Solder
Color Black	Contact Finish - Post (Mating)	Gold
	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Report errors?	Color	Black
		Report errors?

#### DWM-32-01-G-D-330 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DWM-32-01-G-D-330 Payment Methods



















## DWM-32-01-G-D-330 Shipping Methods













If you have any question about DWM-32-01-G-D-330, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com