

#### DWM-39-52-S-S-250 Information

Heisener.com

For Reference Only

Part Number DWM-39-52-S-S-250

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

**Description** .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### DWM-39-52-S-S-250 Specifications

Manufacturer Part NumberDWM-39-52-S-S-250ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWMNumber of Positions39Pitch0.050" (1.27mm)Number of Rows1Row Spacing-Length - Overall0.425" (10.80mm)Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)ColorBlack		
Category         Connectors, Interconnects           Rectangular Connectors - Board Spacers, Stackers (Board to Board)           Package         -           Series         Flex Stack, DWM           Number of Positions         39           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30µin (0.76µm)	Manufacturer Part Number	DWM-39-52-S-S-250
Package-SeriesFlex Stack, DWMNumber of Positions39Pitch0.050" (1.27mm)Number of Rows1Row Spacing-Length - Overall0.425" (10.80mm)Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Manufacturer	Samtec Inc.
Package         -           Series         Flex Stack, DWM           Number of Positions         39           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30µin (0.76µm)	Category	Connectors, Interconnects
Series         Flex Stack, DWM           Number of Positions         39           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30μin (0.76μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions         39           Pitch         0.050" (1.27mm)           Number of Rows         1           Row Spacing         -           Length - Overall         0.425" (10.80mm)           Length - Post (Mating)         0.055" (1.40mm)           Length - Stack Height         0.250" (6.35mm)           Length - Tail         0.120" (3.05mm)           Mounting Type         Through Hole           Termination         Solder           Contact Finish - Post (Mating)         Gold           Contact Finish Thickness - Post (Mating)         30μin (0.76μm)	Package	-
Pitch       0.050" (1.27mm)         Number of Rows       1         Row Spacing       -         Length - Overall       0.425" (10.80mm)         Length - Post (Mating)       0.055" (1.40mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Series	Flex Stack, DWM
Number of Rows       1         Row Spacing       -         Length - Overall       0.425" (10.80mm)         Length - Post (Mating)       0.055" (1.40mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Number of Positions	39
Row Spacing       -         Length - Overall       0.425" (10.80mm)         Length - Post (Mating)       0.055" (1.40mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Pitch	0.050" (1.27mm)
Length - Overall       0.425" (10.80mm)         Length - Post (Mating)       0.055" (1.40mm)         Length - Stack Height       0.250" (6.35mm)         Length - Tail       0.120" (3.05mm)         Mounting Type       Through Hole         Termination       Solder         Contact Finish - Post (Mating)       Gold         Contact Finish Thickness - Post (Mating)       30μin (0.76μm)	Number of Rows	1
Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Row Spacing	-
Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Overall	0.425" (10.80mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Post (Mating)	0.055" (1.40mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)30μin (0.76μm)	Length - Stack Height	0.250" (6.35mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 30μin (0.76μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	30μin (0.76μm)
	Color	Black
Report errors?		Report errors?

### DWM-39-52-S-S-250 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DWM-39-52-S-S-250 Payment Methods



















## DWM-39-52-S-S-250 Shipping Methods













If you have any question about DWM-39-52-S-S-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com