

DWM-42-52-G-D-200 Information

Heisener.com

For Reference Only

Part Number DWM-42-52-G-D-200

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

Description .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DWM-42-52-G-D-200 Specifications

Manufacturer Part Number Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package Series Flex Stack, DWM Number of Positions Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall Length - Post (Mating) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) Louin (0.25um)		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DWM Number of Positions 84 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Manufacturer Part Number	DWM-42-52-G-D-200
Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package	Manufacturer	Samtec Inc.
Package - Series Flex Stack, DWM Number of Positions 84 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Category	Connectors, Interconnects
Series Flex Stack, DWM Number of Positions 84 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions 84 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Package	-
Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Series	Flex Stack, DWM
Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Number of Positions	84
Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Pitch	0.050" (1.27mm)
Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Number of Rows	2
Length - Post (Mating) 0.105" (2.68mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.200" (5.08mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold	Length - Overall	0.425" (10.80mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold	Length - Post (Mating)	0.105" (2.68mm)
Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold	Length - Stack Height	0.200" (5.08mm)
Termination Solder Contact Finish - Post (Mating) Gold	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating) Gold	Mounting Type	Through Hole
-	Termination	Solder
Contact Finish Thickness - Post (Mating) 10uin (0.25um)	Contact Finish - Post (Mating)	Gold
τομιί (0.25μιί)	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Color Black	Color	Black
Report errors?		Report errors?

DWM-42-52-G-D-200 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DWM-42-52-G-D-200 Payment Methods



















DWM-42-52-G-D-200 Shipping Methods













If you have any question about DWM-42-52-G-D-200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com