

DWM-44-52-G-D-250 Information

Heisener.com

For Reference Only

Part Number DWM-44-52-G-D-250

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

Description .050" BOARD SPACERS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DWM-44-52-G-D-250 Specifications

| Manufacturer Part Number DWM-44-52-G-D-250 Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DWM Number of Positions 88 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | | |
|--|--|---|
| Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DWM Number of Positions 88 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10µin (0.25µm) | Manufacturer Part Number | DWM-44-52-G-D-250 |
| Package-SeriesFlex Stack, DWMNumber of Positions88Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.425" (10.80mm)Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm) | Manufacturer | Samtec Inc. |
| Package - Series Flex Stack, DWM Number of Positions 88 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Category | Connectors, Interconnects |
| Series Flex Stack, DWM Number of Positions 88 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | | Rectangular Connectors - Board Spacers, Stackers (Board to Board) |
| Number of Positions 88 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Package | - |
| Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Series | Flex Stack, DWM |
| Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Number of Positions | 88 |
| Row Spacing 0.100" (2.54mm) Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Pitch | 0.050" (1.27mm) |
| Length - Overall 0.425" (10.80mm) Length - Post (Mating) 0.055" (1.40mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Number of Rows | 2 |
| Length - Post (Mating)0.055" (1.40mm)Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm) | Row Spacing | 0.100" (2.54mm) |
| Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm) | Length - Overall | 0.425" (10.80mm) |
| Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm) | Length - Post (Mating) | 0.055" (1.40mm) |
| Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm) | Length - Stack Height | 0.250" (6.35mm) |
| Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Length - Tail | 0.120" (3.05mm) |
| Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Mounting Type | Through Hole |
| Contact Finish Thickness - Post (Mating) 10μin (0.25μm) | Termination | Solder |
| | Contact Finish - Post (Mating) | Gold |
| C.1 | Contact Finish Thickness - Post (Mating) | 10μin (0.25μm) |
| Color Black | Color | Black |
| Report errors? | | Report errors? |

DWM-44-52-G-D-250 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DWM-44-52-G-D-250 Payment Methods



















DWM-44-52-G-D-250 Shipping Methods













If you have any question about DWM-44-52-G-D-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com