

## **DY060-D Information**

Heisener.com

For Reference Only

Part Number DY060-D

Manufacturer Curtis Industries

Category

Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** 

AC/DC CONVERTER 3.3V 5V 12V 60W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DY060-D Specifications**

Manufacturer Part Number         DY060-D           Manufacturer         Curtis Industries           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         Tri-Mag, DY060           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)           Report errors?	•	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         Tri-Mag, DY060           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Manufacturer Part Number	DY060-D
Package         -           Series         Tri-Mag, DY060           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Manufacturer	Curtis Industries
Package         -           Series         Tri-Mag, DY060           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         Tri-Mag, DY060           Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         3           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         5V           Voltage - Output 3         12V           Voltage - Output 4         -           Current - Output (Max)         5A, 4A, 1A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         -           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Package	-
Number of Outputs3Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 1 $3.3\text{V}$ Voltage - Output 2 $5\text{V}$ Voltage - Output 3 $12\text{V}$ Voltage - Output 4-Current - Output (Max) $5\text{A}$ , $4\text{A}$ , $1\text{A}$ Power (Watts) $60\text{W}$ ApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $4.50^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.18^{\circ}\text{H} (114.3 \text{mm} \times 63.5 \text{mm} \times 30.0 \text{mm})$	Series	Tri-Mag, DY060
Voltage - Input90 ~ 264 VACVoltage - Output 13.3VVoltage - Output 25VVoltage - Output 312VVoltage - Output 4-Current - Output (Max)5A, 4A, 1APower (Watts)60WApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 70°C (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  5V  Voltage - Output 3  12V  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  3.3V  3.3V  3.3V  5V  Courtent - Output (Max)  5V  6V  - Current - Output (Max)  5A, 4A, 1A  60W  Commercial)  Fe (Commercial)  Voltage - Isolation  - Chassis Mount  Size / Dimension  4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Number of Outputs	3
Voltage - Output 2 Voltage - Output 3 12V  Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial)  Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating)  Features Universal Input  Mounting Type Size / Dimension  5V  12V  - Chassis Mount 12V	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  SA, 4A, 1A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  12V  - Current - Output (Max)  - Commercial (Max)  - Commerc	Voltage - Output 1	3.3V
Voltage - Output 4  Current - Output (Max)  5A, 4A, 1A  Power (Watts)  60W  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  -  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -  Current - Output (Max)  5A, 4A, 1A  -  60W  Cowmercial  -  Universall  -  Commercial)  -  Commercial  -	Voltage - Output 2	5V
Current - Output (Max)  5A, 4A, 1A  Power (Watts)  60W  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  -  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5A, 4A, 1A  60W  Universial Input  Commercial)  -  Commercial  Commercial	Voltage - Output 3	12V
Power (Watts) 60W  Applications ITE (Commercial)  Voltage - Isolation -  Efficiency -  Operating Temperature 0°C ~ 70°C (With Derating)  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation -  Efficiency -  Operating Temperature 0°C ~ 70°C (With Derating)  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Current - Output (Max)	5A, 4A, 1A
Voltage - Isolation  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Power (Watts)	60W
Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $4.50$ " L x $2.50$ " W x $1.18$ " H ( $114.3$ mm x $63.5$ mm x $30.0$ mm)	Voltage - Isolation	-
Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.50" L x 2.50" W x 1.18" H (114.3mm x 63.5mm x 30.0mm)
		Report errors?

#### **DY060-D Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **DY060-D Payment Methods**



















## **DY060-D Shipping Methods**













If you have any question about DY060-D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com