

DZ100-18 Information

Heisener.com

Part Number DZ100-18

Manufacturer Curtis Industries

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 3.3V 100W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DZ100-18 Specifications

Manufacturer Part Number DZ100-18 Manufacturer Curtis Industries Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DZ100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Tri-Mag, DZ100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Manufacturer Part Number	DZ100-18
Package - Series Tri-Mag, DZ100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Manufacturer	Curtis Industries
Package - Series Tri-Mag, DZ100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Tri-Mag, DZ100 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 25A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Series	Tri-Mag, DZ100
Voltage - Input Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Mounting Type Size / Dimension 90 ~ 264 VAC 3.3V 1.3V 1.3	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Operating Temperature PFC, Universal Input Mounting Type Size / Dimension 3.3V 3.3V 3.3V 3.3V Chassis Mount Current - Output (Max) - Current - Output (Max) - Commercial) - Commercial) - Commercial) - Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Voltage - Isolation - Efficiency Operating Temperature PFC, Universal Input Mounting Type Size / Dimension - Current - Output (Max) - Current - Output (Max) - Current - Output (Max) - Commercial) Commercial) - C	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - Commercial) - Commercial	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - 25A Power (Watts) - Commercial) - Commercial - Commercia	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 25A 100W OW OW TE (Commercial) - Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 100W 10	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Current - Output (Max)	25A
Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Power (Watts)	100W
Efficiency Operating Temperature 0°C ~ 70°C (With Derating) Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°C (With Derating)FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Voltage - Isolation	-
Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)	Features	PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.18" H (127.0mm x 76.2mm x 30.0mm)
		Report errors?

DZ100-18 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DZ100-18 Payment Methods



















DZ100-18 Shipping Methods













If you have any question about DZ100-18, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com