

Heisener.com

E2AX-M12KS04-M1-C1

E2AX-M12KS04-M1-C1 Information

Part Number E2AX-M12KS04-M1-C1
Manufacturer Omron Automation and Safety

Category Sensors, Transducers Proximity Sensors

Description INDUCTIVE SENSOR M12 4MM NPN NO

Package Cylinder, Threaded - M12

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E2AX-M12KS04-M1-C1 Specifications

Manufacturer Part Number E2AX-M12KS04-M1-C1 Manufacturer Omron Automation and Safety Category Sensors, Transducers Proximity Sensors Package Cylinder, Threaded - M12 Series E2A Sensor Type Inductive Sensing Distance 0.157" (4mm) Output Type NPN-NO, 3-Wire Response Frequency 1kHz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12		
Category Sensors, Transducers Proximity Sensors Package Cylinder, Threaded - M12 Series E2A Sensor Type Inductive Sensing Distance 0.157" (4mm) Output Type NPN-NO, 3-Wire Response Frequency IkHz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Operating Temperature Ingress Protection Ingress Protection Ingress Protection Indicator LED Package / Case Sensors, Transducers Proximity Sensors Proximity Sensors Proximity Sensors Notlage - M12 Sensors, Transducers Proximity Sensors Notlage - M12	Manufacturer Part Number	E2AX-M12KS04-M1-C1
Proximity Sensors Package Cylinder, Threaded - M12 Series E2A Sensor Type Inductive Sensing Distance 0.157" (4mm) Output Type NPN-NO, 3-Wire Response Frequency 1kHz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M12SeriesE2ASensor TypeInductiveSensing Distance0.157" (4mm)Output TypeNPN-NO, 3-WireResponse Frequency1kHzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 32 VTermination StyleConnectorOperating Temperature-40°C ~ 70°CIngress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M12	Category	Sensors, Transducers
Series E2A Sensor Type Inductive Sensing Distance 0.157" (4mm) Output Type NPN-NO, 3-Wire Response Frequency IkHz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12		Proximity Sensors
Sensor Type Sensing Distance Output Type NPN-NO, 3-Wire Response Frequency IkHz Shielding Shielded Material - Body Voltage - Supply Termination Style Operating Temperature Ingress Protection Ingress Protection Indicator Package / Case Ingress Connector Cylinder, Threaded - M12	Package	Cylinder, Threaded - M12
Sensing Distance 0.157" (4mm) Output Type NPN-NO, 3-Wire Response Frequency 1kHz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Series	E2A
Output Type Response Frequency 1kHz Shielding Shielded Material - Body Voltage - Supply Termination Style Operating Temperature Ingress Protection Indicator Package / Case NPN-NO, 3-Wire 1kHz Shielded Nickel-Plated Brass Vickel-Plated Brass Voltage - Supply 10 V ~ 32 V Connector -40°C ~ 70°C IP65 LED Cylinder, Threaded - M12	Sensor Type	Inductive
Response Frequency Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Sensing Distance	0.157" (4mm)
Shielding Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 32 V Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Output Type	NPN-NO, 3-Wire
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Response Frequency	1kHz
Voltage - Supply $10 \ V \sim 32 \ V$ Termination Style $Connector$ Operating Temperature $-40^{\circ}C \sim 70^{\circ}C$ Ingress Protection $IP65$ Indicator LED Package / Case $Cylinder, Threaded - M12$	Shielding	Shielded
Termination Style Connector Operating Temperature -40°C ~ 70°C Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Material - Body	Nickel-Plated Brass
Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ingress ProtectionIP65IndicatorLEDPackage / CaseCylinder, Threaded - M12	Voltage - Supply	10 V ~ 32 V
Ingress Protection IP65 Indicator LED Package / Case Cylinder, Threaded - M12	Termination Style	Connector
Indicator LED Package / Case Cylinder, Threaded - M12	Operating Temperature	-40°C ~ 70°C
Package / Case Cylinder, Threaded - M12	Ingress Protection	IP65
-	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M12
		Report errors?

E2AX-M12KS04-M1-C1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E2AX-M12KS04-M1-C1 Payment Methods



















E2AX-M12KS04-M1-C1 Shipping Methods













If you have any question about E2AX-M12KS04-M1-C1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com