

E2B-M12KN05-WP-B2 5M Information

Heisener.com	Manufacturer Category Description	E2B-M12KN05-WP-B2 5M Omron Automation and Safety Sensors, Transducers Proximity Sensors SINGLE M12 SHORT PW 5M PNP NC Cylinder, Threaded - M12 For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



E2B-M12KN05-WP-B2 5M Specifications

Manufacturer Part NumberE2B-M12KN05-WP-B2 5MManufacturerOmron Automation and SafetyCategorySensors, TransducersProximity SensorsProximity SensorsPackageCylinder, Threaded - M12SeriesE2BSensor TypeInductiveSensing Distance0.197" (5mm)Output TypeS0HzResponse FrequencyS0HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIndicatorLEDPackage / CaseCylinder, Threaded - M12		
CategorySensors, TransducersProximity SensorsPackageCylinder, Threaded - M12SeriesE2BSensor TypeInductiveSensing Distance0.197" (Smm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshielded BrassMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating TemperatureP67IndicatorLEDPackage / CaseSylinder, Threaded - M12	Manufacturer Part Number	E2B-M12KN05-WP-B2 5M
Proxinity SensorsPackageCylinder, Threaded - M12SeriesE2BSensor TypeInductiveSensing Distance0.197" (5mm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIEDPackage / CaseCylinder, Threaded - M12	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M12SeriesE2BSenor TypeInductiveSensing Distance0.197" (5mm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - SupplyCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Category	Sensors, Transducers
SeriesE2BSensor TypeInductiveSensing Distance0.197" (5mm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply01 V ~ 30 VTermination StyleCable LeadsOperating Temperature167Ingress ProtectionLEDMaterial - CaseCulter Annual Content Conte		Proximity Sensors
Sensor TypeInductiveSensing Distance0.197" (5mm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply0 V ~ 30 VTermination StyleCable LeadsOperating TemperatureP67Ingress ProtectionLEDPackage / CaseCylinder, Threaded - M12	Package	Cylinder, Threaded - M12
Sensing Distance0.197" (5mm)Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Series	E2B
Output TypePNP-NC, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Sensor Type	Inductive
Response Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Sensing Distance	0.197" (5mm)
NieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Output Type	PNP-NC, 3-Wire
Material - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Response Frequency	800Hz
Voltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Shielding	Unshielded
Termination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Material - Body	Nickel-Plated Brass
Operating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Voltage - Supply	10 V ~ 30 V
Ingress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Termination Style	Cable Leads
IndicatorLEDPackage / CaseCylinder, Threaded - M12	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M12	Ingress Protection	IP67
-	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M12
		Report errors?

E2B-M12KN05-WP-B2 5M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

E2B-M12KN05-WP-B2 5M Payment Methods



If you have any question about E2B-M12KN05-WP-B2 5M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com