

E2B-M12LN08-WP-B1 5M

E2B-M12LN08-WP-B1 5M Information



For Reference Only

Part Number E2B-M12LN08-WP-B1 5M
Manufacturer Omron Automation and Safety

Category Sensors, Transducers Proximity Sensors

Description DOUBLE M12 LONG PW 5M PNP NO

Package Cylinder, Threaded - M12

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E2B-M12LN08-WP-B1 5M Specifications

ManufacturerOmron Automation and SafetyCategorySensors, TransducersProximity SensorsPackageCylinder, Threaded - M12SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NO, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12		
Category Sensors, Transducers Proximity Sensors Package Cylinder, Threaded - M12 Series E2B Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Operating Temperature Ingress Protection Ingress Protection Indicator LED Package / Case Sensors, Transducers Proximity Sensors Vollage - M12 Sensors Inductive LED Package / Case Cylinder, Threaded - M12	Manufacturer Part Number	E2B-M12LN08-WP-B1 5M
Proximity Sensors Package Cylinder, Threaded - M12 Series E2B Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Operating Temperature -25°C ~ 70°C Ingress Protection Indicator LED Package / Case Cylinder, Threaded - M12	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M12SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NO, 3-WireResponse Frequency800HzShieldingUnshieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M12	Category	Sensors, Transducers
Series E2B Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12		Proximity Sensors
Sensor Type Sensing Distance Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature Ingress Protection Indicator Package / Case Ingress Case Inductive Induction Inductive Induction	Package	Cylinder, Threaded - M12
Sensing Distance 0.315" (8mm) Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12	Series	E2B
Output Type PNP-NO, 3-Wire Response Frequency 800Hz Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12	Sensor Type	Inductive
Response Frequency Shielding Unshielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12	Sensing Distance	0.315" (8mm)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Output Type	PNP-NO, 3-Wire
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Response Frequency	800Hz
Voltage - Supply $10\ V \sim 30\ V$ Termination Style $Cable\ Leads$ Operating Temperature $-25^{\circ}C \sim 70^{\circ}C$ Ingress Protection $IP67$ Indicator LED Package / Case $Cylinder, Threaded - M12$	Shielding	Unshielded
Termination Style Cable Leads Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12	Material - Body	Nickel-Plated Brass
$ \begin{array}{lll} \mbox{Operating Temperature} & -25^{\circ}\mbox{C} & \\ \mbox{Ingress Protection} & \mbox{IP67} & \\ \mbox{Indicator} & \mbox{LED} & \\ \mbox{Package / Case} & \mbox{Cylinder, Threaded - M12} & \\ \end{array} $	Voltage - Supply	10 V ~ 30 V
Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M12	Termination Style	Cable Leads
IndicatorLEDPackage / CaseCylinder, Threaded - M12	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M12	Ingress Protection	IP67
•	Indicator	LED
	Package / Case	Cylinder, Threaded - M12
Report errors?		Report errors?

E2B-M12LN08-WP-B1 5M Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E2B-M12LN08-WP-B1 5M Payment Methods



















E2B-M12LN08-WP-B1 5M Shipping Methods













If you have any question about E2B-M12LN08-WP-B1 5M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com