

E2B-M18KS08-WP-B2 5M

E2B-M18KS08-WP-B2 5M Information



For Reference Only

Part Number	E2B-M18KS08-WP-B2 5M	
Manufacturer	Omron Automation and Safety	
Category	Sensors, Transducers Proximity Sensors	
Description	DOUBLE M18 SHORT PW 5M PNP NC	
Package	Cylinder, Threaded - M18	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



E2B-M18KS08-WP-B2 5M Specifications

Manufacturer Part Number E2B-M18KS08-WP-B2 5M Manufacturer Omron Automation and Safety Category Sensors, Transducers Proximity Sensors Proximity Sensors Package Cylinder, Threaded - M18 Series E2B Sensor Type Inductive Sensig Distance 0.315" (8mm) Output Type Sold Response Frequency Sold Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M18		
CategorySensors, TransducersProximity SensorsPackageCylinder, Threaded - M18SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse FrequencySoOHzShieldingNickel-Plated BrassMaterial - Body10 V ~ 30 VVoltage - Supply10 V ~ 30 VOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Manufacturer Part Number	E2B-M18KS08-WP-B2 5M
PackageProxinity SensorsPackageCylinder, Threaded - M18SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M18SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIndicatorLEDPackage / CaseCylinder, Threaded - M18	Category	Sensors, Transducers
SeriesE2BSensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination Style-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18		Proximity Sensors
Sensor TypeInductiveSensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating TemperatureP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Package	Cylinder, Threaded - M18
Sensing Distance0.315" (8mm)Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Series	E2B
Output TypePNP-NC, 3-WireResponse Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Sensor Type	Inductive
Response Frequency500HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Sensing Distance	0.315" (8mm)
ShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Output Type	PNP-NC, 3-Wire
Material - BodyNickel-Plated BrassVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Response Frequency	500Hz
Voltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Shielding	Shielded
Termination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Material - Body	Nickel-Plated Brass
Operating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Voltage - Supply	10 V ~ 30 V
Ingress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M18	Termination Style	Cable Leads
IndicatorLEDPackage / CaseCylinder, Threaded - M18	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M18	Ingress Protection	IP67
	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M18
		Report errors?

E2B-M18KS08-WP-B2 5M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER



E2B-M18KS08-WP-B2 5M Shipping Methods



If you have any question about E2B-M18KS08-WP-B2 5M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com